

1/3" Vandal Resistant Fixed Dome
Camera



FEATURES

- 530 TVL Horizontal Resolution
- DSP (Digital Signal Processor)
- 3 Way Axis Gimbal, wall mountable
- Lens: f = 3.8 mm
- Weatherproof Outdoor Installation (IP66)
- Power Input DC12V

SPECIFICATIONS

Image Sensor	1/3" CCD (Super HAD PIXIM WDR)
Scanning System	PAL, 50Hz, 2:1 Inter Line Transfer
Pixels - total	795 x 596
Pixels - Effective	752 x 582
Resolution	530 (H) lines
Sensitivity	0.3 lux @ F1.4
S/N Ratio	48 dB
BLC	On/Off
AGC	On
White Balance	ATW, AWC
Lens Focal Length	3.8 mm
Lens Drive Type	DC auto iris
Shutter Speed	1/50 sec to 1/100,000 sec
Protection Rating	IP66
Video Outputs	1 CVBS, 1Vpp, BNC
Operating Temperature	-10°C ~ +50°C
Supply Voltage	12 VDC
Power Consumption	1.8 W
Weight	0.75 kg
Dimensions w*h*d	Ø 85 x 68 mm

Design and specifications are subject to change without notice

Status 02/2009