



---

## FEATURES

---

- Displays a full, flat 19" (48cm) diagonal image
- Deterrent Equipment
- Plug & Play Installation (Only a plug need)
- WDR (Wide Dynamic Range) for extreme backlight situations

---

## SUMMARY

---

Here is the new LCD monitor AASSET-security, with built-in camera. As a first real product of deterrence, it is also designed for radiation sensitive. Designed to be installed at the entrance of shops or on the shelves sensitive monitor with this camera is a tool of deterrence against any form of malice. It helps prevent visitors to the outside and inside through technology WDR (against extreme-days) of its integrated camera Varifocal.

---

## SPECIFICATIONS

---

---

**SPECIFICATIONS**

---

Video Standard	PAL
LCD Panel size	19" Diagonal AM-TFT
Display protection	Tempered Glass
Scanning System	Progressive
Brightness	300 cd/m <sup>2</sup>
Contrast ratio	1000:1
Response Time	5 ms
Viewing Angle	80°(L)80°(R)80°(T)80°(B)
Video Inputs	2 BNC, 1 VGA
Resolution	800 x 600
Screen Mode	4:3
Underscan	On/Off
PIP	On/Off
Audio Inputs	1 CH, RCA, Line Level 10kOhms
Speaker Output	2 W

---

---

**SPECIFICATIONS**

---

## Camera Functions

Image Sensor	1/3" CMOS PIXIM (WDR)
Resolution	480 (H) lines
Sensitivity	0.3 lux @ F1.2 (0.002 lux sens up x128)
Lens Focal Length	4 ~ 9 mm (65°~29°)
Motion Detection	On/Off/Area Setting
Operating Temperature	10°C ~ +40°C
Humidity	10 ~ 80%RH
Storage Temperature	-20°C ~ +45°C
Storage Humidity	5% ~ 95%, non-condensing
Supply Voltage	230 VAC
Dimensions w*h*d	500 x 465 x 76 mm

---

**ACCESSORIES**

---

**AST BRLCD2405**  
Monitor Bracket**AST BRLCD2453**  
Monitor Bracket