

1/3" CCD Colour Network Camera



## FEATURES

- Hybride camera (both video output analog & IP)
- H264 compression mode (Owner 25 fps max)
- Video motion detection
- SD memory card slot for alarm image recording
- Easy Network Setup such as TCP/IP, HTTP, DHCP, DNS, RTP/PTCP, PPOE
- 535 TVL Horizontal Resolution
- Accepts 2 types of auto iris lenses (DC/Video)
- Bidirectional Audio Support
- Power Input DC12V
- Web Viewer by Internet Explorer or by Software included

## SPECIFICATIONS

Image Sensor	1/3" CCD (Super HAD PIXIM WDR)
Scanning System	PAL, 50Hz, 2:1 Inter Line Transfer
Pixels - total	795 x 596
Pixels - Effective	752 x 582
Resolution	535 (H) lines
Sensitivity Colour	0.1 lux @ F1.2
Day/Night	Auto/Electronic
Motion Detection	On/Off/Sensitivity
AGC	Off, Low, Middle, High
ELC	Off, Auto x 2, Auto x 5
Camera ID	32 character
White Balance	ATW
Lens Mount	C/CS mount with adaptor
Lens Drive Type	Auto iris, DC, VS
Video Outputs	1 CVBS, 1Vpp, BNC
Alarm Inputs	1
Alarm Outputs	1

Design and specifications are subject to change without notice

Status 03/2009

1/3" CCD Colour Network Camera

**SPECIFICATIONS**

Remote Control	RS 485, addressable, multiprotocoll
Operating System	Embedded Linux
Client OS	Win 2000 / XP / VISTA
Web Browser	MS Internet Explorer 5.0 (or higher)
Video Compression	H264 dual compression stream
Audio Compression	OggVorbis 16Kbps
Network Streaming	TCP, UDP (Unicast, Multicast)
Network Protocol	TCP, UDP, RTP, Multicast, HTTP, DHCP, PPPoE, etc
Video Resolution	4CIF (704x576), 2CIF (704x288), DCIF (528x384), CIF (352x288), QCIF (176x144)
Frame Rate	25/22/20/18/16/15/12/10/8/6/4/2/1/0.5/0.25/0.12/0.06 fps
Alarm Event	Alarm Input, Motion Detection or Schedule: Image transfer FTP
IP Installer	IP Address Installation Function (Win XP, VISTA & 2000 support)
Firmware Upgrade	Firmware upgrade by Web Browser
Login Access Level	The administrator can create up to 15 separate users with different right levels
Time Setting	Setting by Software local or internet
Recording	H264
HTTP API	Provides functionality to control cameras and set/retrieve internal parameter values.
Windows API	ActiveX components for viewing streams from video camera.
Input/Output sockets	Power(jack), RJ-45, SD Card Slot, Terminal 6Pin(Alarm In 2Pin, Alarm Out 2Pin, RS485 2Pin)
Operating Temperature	-10°C ~ +60°C
Humidity	less than 90%
LED Indicator	Yes
Supports	SD Card
Supply Voltage	12 VDC
AGC	Off, Low, Middle, High
Power Consumption	5 W
Weight	0.6 kg
Dimensions w*h*d	65 x 67 x 122 mm



Design and specifications are subject to change without notice

Status 03/2009

1/3" CCD Colour Network Camera

## REAR VIEW

