

# BreezeACCESS® 900

## Broadband Access for Mobile Public Safety and Foliage-Dense Areas

Supporting both fixed and mobile subscribers, BreezeACCESS 900 offers operators important opportunities for additional revenue sources. Designed to provide coverage in areas with many obstructions such as trees that block line-of-sight, BreezeACCESS 900 is an effective, real-time mobile and fixed communication system for use by public safety agencies. Whether trying to connect police cars, ambulances, fire trucks, or other emergency vehicles to the public safety network, or wanting to provide a network connection to residential users in areas where signals might otherwise be obstructed, BreezeACCESS 900 is the ideal solution.

### Product Highlights

To ensure fast, consistently reliable data and voice services, the BreezeACCESS 900 features a comprehensive range of technology and product benefits including:

#### More customers more revenues

In many areas, reaching potential customers with broadband wireless can be greatly limited due to dense foliage, which obstructs the broadband signal. BreezeACCESS 900 immediately increases the percentage of servable customers, resulting in the ability to tap a significant new source of revenue.

#### Minimal capital investment:

Even better, BreezeACCESS 900 allows existing BreezeACCESS-based Alvarion operators to serve additional customers with no modification of their base station sites at all. When deployed using the cell extender (CX) option, BreezeACCESS 900 requires minimal capital investment while fully leveraging existing BreezeACCESS deployments in both the 2.4 and 5 GHz bands.

#### Mobile public safety option:

BreezeACCESS 900 is also specially designed to support mobile subscribers. Secure, robust and reliable mobile access over metro or rural areas can be created with 10 times less infrastructure than mesh systems.

#### Field proven features:

Designed with field-proven features, such as hybrid digital modulation to achieve superior range, reliability, and flexibility, BreezeACCESS 900 enables carriers to customize frequency operation away from sources of interference. It also features variable antenna polarity, as well as a comprehensive built-in spectrum analyzer utility for site surveys, network planning, system configuration and troubleshooting.

#### The benefits of belonging to Alvarion's Complete Spectrum™ Solution:

Part of Alvarion's Complete Spectrum solution, the BreezeACCESS 900 integrates seamlessly with existing BreezeACCESS deployments and leverages the capacity of BreezeACCESS 2.4 and 5 GHz networks. As a result, operators can significantly increase their revenues by growing their networks and subscriber base with little additional investment.

### Additional Product Highlights

- CX architecture to leverage operational BreezeACCESS networks
- Range of 2-3 miles in NLOS and 1/2 mile through very heavy foliage
- Customizable frequency agility and time diversity for unmatched interference immunity
- Excellent sensitivity for longer links and better foliage penetration
- Spectrum analyzer utility and full LED diagnostics for easy antenna alignment and association count
- Ethernet port for local subscriber acquisition
- Remote telnet, SNMP, or local serial port management
- Integrated 16 dBI antenna on backhaul radio for faster deployment
- External antennas on access units for flexible deployment of coverage
- Mobile subscriber options designed for in-vehicle installation



**International Corporate Headquarters**

Tel: +972 3 6456262  
Email: corporate-sales@alvarion.com

**North America Headquarters**

Tel: +1 650 314 2500  
Email: n.america-sales@alvarion.com

**Latin America & Caribbean**

Tel: +1 954 746 7420  
Email: lasales@alvarion.com

**Brazil**

Tel: +55 41 3024 6665  
Email: brazil-sales@alvarion.com

**China**

Tel: +86 10 8857 6770  
Email: china-sales@alvarion.com

**Czech Republic**

Tel: +420 222 191 233  
Email: czech-sales@alvarion.com

**France**

Tel 1: +33 1 49 38 91 91  
Tel 2: +33 1 34 38 54 30  
Email: france-sales@alvarion.com

**Germany**

Tel: +49 89 90405 923  
Email: germany-sales@alvarion.com

**Ireland**

Tel: +353 66 712 8004  
Email: uk-sales@alvarion.com

**Japan**

Tel: +81 3 3761 7206  
Email: japan-sales@alvarion.com

**Mexico**

Tel: +52 55 5340 1421  
Email: mexico-sales@alvarion.com

**Philippines**

Tel: +632 754 8028  
Email: far.east-sales@alvarion.com

**Poland**

Tel: +48 22 863 28 78 / 80  
Email: poland-sales@alvarion.com

**Romania**

Tel: +40 21 266 47 31  
Email: romania-sales@alvarion.com

**Russia**

Tel: +7 095 783 82 31  
Email: info@alvarion.ru

**Singapore**

Tel: +65 9631 4700  
Email: far.east-sales@alvarion.com

**South Africa**

Tel: +27 12 6728836  
Email: africa-sales@alvarion.com

**U.K.**

Tel: +44 845 450 1414  
Email: uk-sales@alvarion.com

**Uruguay**

Tel: +598 2 606 2651  
Email: lasales@alvarion.com

## Specifications

### 900 MHz Radio

Frequency	902- 928 MHz ISM band		
Operation mode	Time Division Duplex (TDD)		
Radio access method	FH-CDMA		
Standard compliance	FCC Part 15.247		
Channel bandwidth	2 MHz		
Central frequency resolution	1 MHz		
SU antenna	10 dBi, 65° x 65° VPOL/HPOL		
AU antenna	13 dBi, 90° x 16°, Sector - Dual polarity		
	10 dBi, 65° x 65°, Flat Panel (H/V)		
	9 dBi Omni, 360° x 10°, VPOL		
Maximum input power (at antenna port)	-20 dBm		
Output power (at antenna port)	23 dBm typical		
Gross bit rate	1, 2, 3 Mbps	SU-I/D	AU-E
Sensitivity, typical (dBm at antenna port, BER 10E-6)	Gross Rate	Sensitivity	Sensitivity
	1 Mbps	-90 dBm	-92 dBm
	2 Mbps	-84 dBm	-87 dBm
	3 Mbps	-77 dBm	-80 dBm
Modulation	GFSK modulation, 2, 4, 8 level (1, 2, 3 bits/symbol)		
Symbol rate	1 Msymbol/sec		

### Data Communication

Standard compliance	IEEE 802.3 CSMA/CD		
VLAN support	Based on IEEE 802.1Q		
Traffic prioritization	Based on IEEE 802.1p, IP ToS according to RFC791		

### Configuration and Management

Management	Via Telnet, SNMP, TFTP		
SNMP agents	SNMP ver 1, MIB II, Bridge & Private MIBs		
Security	RC4 WEP option (encryption of the authentication process)		
	VLAN according to IEEE 802.1Q		
	IP address filtering for management		
Authentication and accounting	RADIUS client in the SU according to RFC 2865 and 2866		
Allocation of IP parameters	Configurable or automatic (DHCP client)		

### Standards Compliance, General

EMC	FCC Parts 15.203, 15.204, 15.207, 15.209		
Safety	IEC 60 950 US/C (TUV), FCC 1.1307		
Environmental	Operation	ETS 300 019 part 2-3 class 3.2E for indoor units	
		ETS 300 019 part 2-4 class 4.1E for outdoor units	
	Storage	ETS 300 019-2-1 class 1.2E	
	Transportation	ETS 300 019-2-2 class 2.3	
Lightning protection (CX antenna connections)	EN 61000-4-5, Class 3 (2kV)		
Radio	FCC part 15.247, 15.203		

### Subscriber Unit Environmental

Operating temperature	0°C to 40°C (32°F to 104° F)		
Operating humidity	5%-95% non condensing		

### Subscriber Unit Mechanical

Metal box, desktop or wall mountable	Dimensions (cm)	Weight (kg)	
	15 x 8.7 x 3.7	0.35	

### Subscriber Unit Electrical

External power supply; AC	100-240 Vr.m.s., 47-63 Hz		
DC power output	5.1V, 2A max.		

### Cell Extender Stand-Alone AU Specifications

Refer to the 2.4 GHz BreezeACCESS II specifications on the 2.4 GHz side and for the stand alone AU. Subscriber 900 MHz specifications are as above.

### IF interface (2.4 GHz and 900 MHz ODU)

IF frequency	440 MHz		
IF cable impedance	50 ohm		
Maximum IF cable attenuation	15dB		
Maximum IF cable DC Resistance	1.5 ohm		

### Environmental

Operating temperature	Interface unit	-10°C to 55°C (-14°F to 131°F)	
	Outdoor unit	-40°C to 55°C (-40°F to 131°F)	
Operating humidity	Outdoor unit	100% RH Condensing	

### Mechanical

Interface unit	Dimensions (cm)	Weight (kg/Lbs)	
	Metal box, wall mountable	28 x 23 x 11	5.9 / 13
Outdoor unit	Metal box, 2"-3" pole mountable	30.6 x 30.6 x 7.2 2.5 / 5.5	

### Electrical

110-240 VAC, 50-60Hz, 1.4A max
--------------------------------



[www.alvarion.com](http://www.alvarion.com)

© Copyright 2005 Alvarion Ltd. All rights reserved.  
Alvarion® and all product and service names referenced here in are either registered trademarks, trademarks, tradenames or service marks of Alvarion Ltd.  
All other names are or may be the trademarks of their respective owners. The content herein is subject to change without further notice.

Features and specifications are subject to change without further notice.