

HD Network Video Recorder Server



Avigilon's end-to-end surveillance solutions deliver image detail no other system can match. Avigilon Control Center software, featuring High-Definition Stream Management™ (HDSM™) technology combined with our broad range of megapixel cameras (from 1 MP to 29 MP) provide unprecedented clarity—while effectively managing storage and bandwidth requirements. Our components are scalable and can work together in an end-to-end system, or can be customized to create your own powerful and cost-effective solution.

The innovative HD network video recorder is just one way Avigilon can help provide the very best monitoring and protection.



Our Network Video Recorders (NVRs) have Avigilon Control Center preloaded and configured for maximum performance and reliability, making them easy to integrate into any Avigilon surveillance system. NVR servers can record up to 32 MB/s of image data from up to 128 cameras.

KEY FEATURES

- Preloaded and configured with Avigilon Control Center High Definition Network Video Management Software
- Records up to 32 MB/s of image data
- Supports up to 128 camera channels
- Supports up to 30 images per second per camera channel
- RAID 5 hard drive configuration
- Up to 15 TB effective recording capacity (after RAID 5 applied) that is expandable using HD-NVR-EXP2
- Hot-swappable hard drives and power supplies
- 4 gigabit Ethernet ports
- 2U rack mount chassis

Specifications

SYSTEM	Control Center Edition	Enterprise, Standard and Core compatible	
	Recording Rate	Up to 32 MB/s	
	Camera Channels	Up to 128	
	Recording Image Rate	Up to 30 images per second per channel, total of 3840 for 128 channels	
	Local Viewing	No	
	Operating System	Microsoft® Windows Embedded Standard 7	
	Hard Disk Drive Configuration	6 near-line SAS, hot-swappable, RAID 5	
	Recording Storage Capacity	Up to 15 TB effective (after RAID 5), expandable using HD-NVR-EXP2	
	Processor	Quad core Intel® Xeon® 2.0 GHz	
	Memory	6 GB RAM (3 x 2GB)	
	Network Interface	4 Gigabit Ethernet RJ-45 ports (1000Base-T)	
	Video Outputs	1 VGA	
	Optical Drive	1 DVD-RW	
	MECHANICAL	Form Factor	2U rack mount chassis
Dimensions (LxWxH)		681 mm x 443 mm x 86 mm; 26.8" x 17.4" x 3.4"	
Weight		26 kg (57.4 lbs)	
ELECTRICAL	Power Input	100 to 240 VAC, 50/60 Hz, auto-switching	
	Power Supply	Single hot-swappable, dual-redundant optional with HD-NVR-2ND-PS	
	Power Consumption	570 W	
ENVIRONMENTAL	Operating Temperature	10° C to 35° C (50° F to 95° F)	
	Storage Temperature	-40° C to 65° C (-40° F to 149° F)	
	Humidity	20 - 80% Relative humidity (non-condensing)	
	Operating Vibration	0.26G at 5 Hz to 350 Hz for 2 minutes	
	Storage Vibration	1.54Grms Random Vibration at 10 Hz to 250 Hz for 15 minutes	
	Operating Shock	1 shock pulse of 41G for up to 2 ms	
	Storage Shock	6 shock pulses of 71G for up to 2 ms	
	Operating Altitude	-16 m to 3048 m (-50 ft to 10,000 ft)	
REMOTE PC CLIENT REQUIREMENTS	Storage Altitude	-16 m to 10,600 m (-50 ft to 35,000 ft)	
	Operating System	Microsoft® Windows® XP with Service Pack (SP) 2 or later, Windows® Vista, or Windows® 7	
	Processor	Intel® Single Core 2.4 GHz (minimum); Intel® Dual Core 2.0 GHz (recommended)	
	Memory	1 GB RAM (minimum); 2 GB RAM (recommended)	
	Video Card	PCI Express, DirectX 9.0c compliant with 128 MB RAM (Intel® GMA 900 or better, NVIDIA® 6600 or better, ATI X1300 or better)	
	Network Interface	100 Mbps (minimum); 1 Gbps (recommended)	
	Hard Disk Space	500 MB	
SUPPLIED ACCESSORIES		Rack mount kit (brackets, rails, and hardware)	
		Cable management arm	
		Rack bezel	
		USB keyboard	
		USB mouse	
		Power cord	
CERTIFICATIONS	Safety	EN 60950-1:2006 + A11:2009 IEC 60950-1:2005 Ed2	EN 62311:2008
	Electromagnetic Emissions	EN 55022:2006 + A1:2007 CISPR 22:2005 + A1:2005 EN 61000-3-2:2006	IEC 61000-3-2:2005 (Class D) EN 61000-3-3:1995 + A1:2001 + A2:2005 IEC 61000-3-3:1994 + A1:2001 + A2:2005
	Electromagnetic Immunity	EN 55024:1998 + A1:2001 + A2:2003	CISPR 24:1997 (modified)+A1:2001 + A2:2002
ORDERING INFORMATION	2.5TB-HD-NVR	2.5 TB storage, Network Video Recorder Server	
	5.0TB-HD-NVR	5.0 TB storage, Network Video Recorder Server	
	10.0TB-HD-NVR	10.0 TB storage, Network Video Recorder Server	
	15.0TB-HD-NVR	15.0 TB storage, Network Video Recorder Server	
	2.5TB-HD-NVR-LPR	2.5 TB storage, Network Video Recorder Server, 2nd processor installed	
	5.0TB-HD-NVR-LPR	5.0 TB storage, Network Video Recorder Server, 2nd processor installed	
	10.0TB-HD-NVR-LPR	10.0 TB storage, Network Video Recorder Server, 2nd processor installed	
	15.0TB-HD-NVR-LPR	15.0 TB storage, Network Video Recorder Server, 2nd processor installed	
	10.0TB-HD-NVR-EC2	10.0 TB storage, Network Video Recorder Server, HD-NVR-EXP2-CARD installed	
	15.0TB-HD-NVR-EC2	15.0 TB storage, Network Video Recorder Server, HD-NVR-EXP2-Card installed	
	HD-NVR-2ND-PS	Secondary redundant power supply	
	HD-NVR-EXP2-CARD	Expansion card for connecting storage expansion to an HD-NVR	
	HD-NVR-EXP2-10TB	10 TB RAID 6 expansion, 2U rack mount	
	HD-NVR-EXP2-20TB	20 TB RAID 6 expansion, 2U rack mount	
	HD-NVR-EXP2-30TB	30 TB RAID 6 expansion, 2U rack mount	
		* Control Center licenses must be purchased separately	