

# AXIS 290A Outdoor housing for Axis Network Cameras

*Camera protection you can rely upon...  
...come rain, shine or grime!*

If you're looking to install Axis network cameras outdoors, you'll need to provide them with the right protection. IP66 classified housings from Axis offer a convenient, durable and tailor-made solution for mounting Axis network cameras outdoors and within other harsh environments. Made with a solid extruded aluminum casing, outdoor camera enclosures from Axis provide robust protection for tamper-proofing your cameras, and shields them against dust and heavy rain. They even incorporate a temperature controlled heating system that ensures continued camera operation in cold weather conditions.

290A Outdoor housing for Axis Network Cameras

Take your surveillance outdoors with tailor-made outdoor enclosures for Axis network cameras.



- Tailor-made enclosure solution for the AXIS 2120, AXIS 2420, AXIS 211, AXIS 211A and AXIS 221 Network Camera
- Weather protected from -20°C to +42°C
- Weatherproof to IP66
- Supplied with integral tamper-proof mounting bracket

# AXIS 290A Outdoor housing for Axis Network Cameras



26388/EN/RS/0602

Specifications		
<b>Models</b>	AXIS 290A: Outdoor temperature controlled camera housing in extruded aluminum. Tailor-made for the AXIS 2120, AXIS 2420, AXIS 211, AXIS 211A and AXIS 221 Network Camera	
<b>Security</b>	Multiple user access levels with password protection, IP address filtering, HTTPS encryption	
<b>Materials</b>	Main body, bracket and sunshield: Aluminum Fastenings, wall fixings and locking clips: Stainless steel Window: Glass Camera mounting board: Bakelite Gaskets: Polyethylene and Neoprene Finish: Polyester powder coating RAL 9002 30% gloss white/grey	
<b>Cable length</b>	<b>Cable length</b>	
	Maximum cable length	Minimum cable area
	330 ft (100m)	AWG* 13 - 0.0040 sq inch (2.6 mm <sup>2</sup> )
	260 ft (80m)	AWG 14 - 0.0031 sq inch (2.0 mm <sup>2</sup> )
	160 ft (50m)	AWG 16 - 0.0020 sq inch (1.3 mm <sup>2</sup> )
100 ft (30m)	AWG 18 - 0.0012 sq inch (0.78 mm <sup>2</sup> )	
	*American Wire Gauge	
<b>Casing</b>	Integral tamper proof wall bracket Weatherproof to IP66	
<b>Power</b>	Input voltage: 100-240 V AC (50/60 HZ) Input current: 0.55 A at 100 V AC / 0.28 A at 240 V AC Minimum power requirement: 68 VA Output voltage: 12 V DC Output current: 1 A	
<b>Operating conditions</b>	Ambient operating temperature: -20°C to +42°C (-4 F to +108 F) Maximum ambient operating temperature for housing mounted in direct sunlight: +35°C (95 F)	
<b>Installation, management and maintenance</b>	This product shall only be installed by a licensed electrician	
<b>Included Accessories</b>	Comes complete with sunshield, power supply and mounting fixings	
<b>Approvals</b>	IP66 CE: EN60950 Power Supply: EMC: FCC class B, CISPR 22 class B, VCCI class B Safety: UL, CSA, CE	
<b>Dimensions and weight</b>	Internal dimensions (H x W x L): 93 x 130 x 300 mm (3.66 x 5.12 x 11.81 inches) External dimensions (H x W x L): 135 x 180 x 410 mm (5.3 x 7.1 x 16.2 inches) Weight: 3.2 kg (7 lbs)	

[www.axis.com](http://www.axis.com)