

# AXIS ACH13HB Outdoor Housing

*Weatherproof your Axis Network Cameras*



The AXIS ACH13HB Outdoor Housing provides protection for Axis network cameras in both hot and cold climates. The housing was designed to meet IP65 standard of protection.

The body is constructed of an attractive white finished aluminum with black end caps.

The housing ships with a 24VAC heater and blower that enables the Axis network camera to operate in temperatures from  $-20^{\circ}$  F to  $+120^{\circ}$  F.



- Indoor and outdoor models
- IP65- rated protection
- 24 VAC heater and blower
- Side hinge for easy access when servicing

# AXIS ACH13HB Outdoor Housing

## Technical Data – Housing

### General

- Made of aluminum
- White finish with black end caps
- Two watertight strain relief valves for network and power cables
- For use with AXIS 211 and AXIS 221 Network Camera

### Electrical

- 24 VAC, 50/60 Hz
- Heater: 24 VAC, 25 vA, 1.04 Amps
- Blower: 24 VAC, input (RECTIFIED), 1.4 vA
- 24 VAC to 12 VDC transformer, 1.0 Amp

### Dimensions and Weight

- Product measurements  
Weight (excluding power supply): 4 lbs  
Dimensions (H x W x D): 15.25 x 4.33 x 5.5 inches
- Shipping measurements  
Weight: 5 lbs  
Dimensions (H x W x D): 17 x 5 x 6 inches

### Operating Conditions

- Indoor/outdoor (Indoor version with no electronics available)  
*The indoor model does not include:  
Heater or blower;  
24vac to 12vdc power supply;  
Sunshield  
Works with the AXIS 210 Network Camera*
- IP65 rated (with cable glands)
- Operating Temperature -20 F to +120 F

### Approvals

- CE
- UL Listed
- 24 VAC, 40 VA Power Supply
- Integrated Sunshield
- Heater and Blower
- Installation Guide

[www.axis.com](http://www.axis.com)