

500 Series Door Entry Telephone

The 500 range of telephones complement our systems and incorporate the extra facilities requested by local authority and public housing.

The telephones are manufactured from high impact white ABS plastic. The white handset cord is coiled with a heavy-duty sleeve and has a plug in connector at the telephone base. No wires or parts are connected to the removable cover so that when it is removed there is no risk of damage. With its wide handset the model 500 telephones are suitable for the elderly.



Model 500D – Desk



Model 500LX



Model 500X

Dimensions: H = 212mm, W = 93mm, D = 55mm

Available models

- 500 **A** 500 **PA**
- 500 **D** 500 **PD**
- 500 **X** 500 **PX**
- 500 **LX** 500 **PLX**
- 500 **XT** 500 **PXT** 500 **LXT** 500 **PLXT**
- 500 **XC** 500 **PXC** 500 **LXC** 500 **PLXC**
- 500 **PH**

A Operation on AC powered systems

D Operation on DC powered systems

P Privacy of Speech

Any conversation between the visitor and the resident on the called telephone is totally private. This feature is highly recommended on systems that have in excess of 20 stations.

X Mute Switch

A button is included to allow the user to mute the call-tone and prevent disturbances from nuisance calls. A red LED indicates the telephone is muted. Clear permanent instructions are provided on the cover.

L Door Status

An additional green LED labeled 'door open' is provided to indicate when the main entrance is open. A N/O door contact is required.

T Mute Timer

Allows the resident to turn the call-tone off for a pre-determined period. The time period can be set at installation to 16 time options up to 8 hours.

C Call Timer

A single push of the call button at the front door panel will produce a timed Call Tone. This time period is adjustable, typically 2 to 10 seconds.

H Door Indicator

The telephone has two LED's labeled DOOR1 and DOOR2 which are illuminated accordingly when called from a panel on a two door system. This allows the tenant to identify the calling door.

Desk

Any of the 500 Series telephones can be supplied for desk-top use. The telephone is manufactured with a steel mounting plate and rubber feet. A pre-wired telephone lead is included with a wall-mounting socket.

e.g. To order a desk mounted 500PA telephone, use the code 500PA-DESK.

Model LS47 Apartment Station

This wall-mounting unit is ideal for residents who cannot use a telephone such as the elderly or arthritic sufferers. It has two large push-button pads; one for 'press to talk' and one for operating the lock release. Since the unit can only be powered from 12 V DC an additional power supply may be required when connecting to an existing AC powered door entry system.

Dimensions: H = 95mm, W = 202mm, D = 30mm

Model LSD47 Apartment Station

This unit offers the same functions as the model LS47 but is adapted for desk-top mounting.

Dimensions: H = 95mm, W = 202mm, D = 58mm

