

BN2009IRIP

iPac Plus Indoor Dome Camera



iPac Plus

Features:

- 1/3" Sony CCD
- Effio-e DSP for advance image processing
- H.264 video compression
- D1 30fps real time recording
- IR effective range up to 140 feet
- Audio compression: G723.1/6.3kbps
- Built-in Micro SD Card slot



ONVIF



Specifications:

Camera	
Image Sensor	1/3" Sony CCD
Digital Signal Processor	New Sony Effio-e
Resolution	600TVL
Minimum Illumination	0.1 Lux(F1.2)
S/N Ratio	48dB
White Balance	AWB/AWB/ANTI-CR/Manual
AGC	High/Middle/Low/Off
BLC	On/Off
Electronic Shutter	1/60~100,000 sec
DNR	2D
Gamma	0.45
Video Output	BNC 75 Ohm, Digital out
Lens	2.8 - 10mm
LEDs	850nm, 140ft effective range
Video	
Compression	H.264,MJPEG
Encode Speed	20Kbps-12Mbps
Encode Resolution	510 x 494 D1@30fps
Stream Range	VBR/CBR 5kb - 2M
Interfaces	
Alarm Input/Output	1/1
Network Interface	RJ-45,10/100Base-t
Network Protocols	RTP/RTCP, TCP/UDP, IPv4/v6, HTTP, DHCP, PPPoE, DDNS
SD Card	Micro SD/HCSd, up to 32GB
PTZ Control	RS485
Audio Input/Output	1/1
Environmental	
Operating temperature	(-14°F ~ 140°F)
operating Humidity	RH90% Max. (Non-condensing)
Electrical	
Input Voltage	DC12V/PoE
Power consumption	<5W,120mA
Mechanical	
Dimensions	ø130mm x 112mm(L*H)
Weight	450g

For more information or technical support, please call (909) 305-8889 or log on to www.bolideco.com

468 South San Dimas Avenue, San Dimas CA 91773 | Tel: (909) 305-8889 Fax: (909) 305-0999

Bolide Technology Group makes no representation concerning the legality of certain product application. We encourage you to check and comply with all applicable local state, and federal laws. Specification and availability are subject to change without notice. All trademarks, registered trademarks, and names are the property of their respective owners.