

CAPTURE



web: www.capturecctv.com

tel: 1-800-471-2003

FEATURES:

- Versatile display formats provide a convenient user interface.
- Full-screen with 2xZoom, 2x2, 3x3, Picture-in-Picture (PIP) display
- Cameras can be assigned to any picture format
- Dual monitor outputs (MAIN and SPOT) allow simultaneous multi-camera and full-screen viewing
- "Dynamic Scene Sensing" motion detection
- On-screen display includes date, time, alarm status, video loss and camera titles
- Capable of live, VCR or preview mode during recording
- User-friendly programmable menus
- Camera alarm input is activated by contact closure or TTL/CMOS signal
- Alarm input polarity is selectable
- Rack mountable (brackets included)
- Control multiple units from 1 keyboard via RS-485 (keyboard optional)
- 3 Year Warranty

CPT-CD9

9-Channel Duplex Color Multiplexer

CAPTURE

Distributed by:

**Richardson
Electronics**
Security Systems Division

1-800-722-CCTV
Please contact your local representative
for additional information.

CPT-CD9

9-Channel Duplex
Color Multiplexer



Specifications:

Video Input	1 Vp-p, 75 Ohm Camera input: 9 EA (BNC)
Video Output	1 Vp-p, 75 Ohm Looping output: 9 EA (BNC) SPOT output: 1 EA (BNC) MAIN output: 1 EA (BNC or Y/C) High Resolution: 720x480 pixels
VCR In/Out	1 Vp-p, 75 Ohm, 1 EA BNC or Y/C
Alarm	DB-25S Female Alarm input: 9 EA Alarm output: 1 EA (NC/NO/COMMON) Alarm hold time: 0-99 sec.; default: 20 sec.
Input power	12VDC, 1.5A
Ambient Temperature	32°F to 95°F 0°C to 35°C
Ambient Humidity	10% to 90% (non-condensing)
Dimensions	17 x 1.75 x 12.25 (in) 432 x 44 x 310 (mm)
Net Weight	6.2 lbs 2.8 kg

TECHNICAL SPECIFICATION

www.capturecctv.com

CAPTURE

1-800-471-2003

CPT0101

All specifications subject to change without notice. Information furnished is believed to be accurate and reliable. However, no responsibility or liability is assumed by its use, nor for any infringement of patents or other rights of third parties which may result from its use.