


## APPEARANCE



## DESCRIPTION

The ComNet™ CNGE28FX4TX24MSPOE+ Layer 2 Managed 28 Port Ethernet Switch supports twenty-four (24) 10/100/1000 Base-TX ports and four (4) 1000Base-FX ports of Ethernet data. Fully compliant with IEEE 802.3at, up to 720 watts of PoE or PoE+ power is available for distribution across all 24 Base-TX ports. The four 1000BASE-FX combination ports are 1000 TX or SFP configurable for fiber type (multimode or single-mode), connector type and distance. The exclusive C-Ring redundant ring feature protects networks from interruptions or temporary malfunctions with its fast recovery technology. Legacy ring allows the switch to be used in an existing ring of ComNet X-Ring enabled switches. eConsole, a powerful, easy-to-use Windows-based utility, allows the CNGE28FX4TX24MSPOE+ to be centrally managed. The electrical ports support the 10/100/1000Mbps Ethernet IEEE 802.3 protocol, and auto-negotiating and auto-MDI/MDIX features are included. The CNGE28FX4TX24MSPOE+ are optically (1000BASE-FX) and electrically compatible with any IEEE 802.3 compliant Ethernet device and are hardened for use in harsh operating environments. Featuring a low-profile 1-RU high rack-mountable package, these units may be mounted within any standard 19-inch rack cabinet, and the high-capacity power supply for operation of the switch and PoE PSE (power Sourcing equipment) is completely self-contained.

## APPLICATIONS

- › HD Surveillance
- › High-Port Count Ethernet Hub Locations for Industrial Automation, Industrial Security and Transportation Networks

## FEATURES

- › IEEE 802.3at Compliant for PSE. Up to 30W of PoE+ power available per port. 720W total PoE power available.
- › 56 Gbps Backplane
- › IGMP v2/v3 (IGMP snooping support) for filtering multicast traffic & Port Trunking for ease of bandwidth management
- › Supports 24 Gigabit Ports, and four 1000BASE-FX optical ports with optional ComNet SFPs
- › Power supply for switch operation and PoE power sourcing is completely self-contained within the switch
- › Fully Compliant with the Environmental Requirements of NEMA TS-1/TS-2 & the Caltrans Specification for Traffic Signal Control Equipment
- › STP/RSTP/MSTP supported
- › Windows utility, eConsole, supports centralized management, and is web-based configurable, or by Telnet and console (CLI) ports
- › Port lock to prevent access from unauthorized MAC address
- › SNMP V1/V2c/V3 for secure network management
- › Fastest Redundant Ethernet Ring: C-Ring. Recovery time <30ms, with > 250 switches within the ring
- › Low-profile 1-RU (1.75-inch) high rack-mountable chassis mounts within any standard 19-inch equipment rack
- › Operating Temperature: -40° to +75° C (-40° to +167° F). Functional to +85° C (185° F)
- › Lifetime Warranty
- › Event notification through Syslog, E-mail, SNMP trap
- › RMON for traffic monitoring
- › Supports LLDP (Link Layer Discovery Protocol)
- › PTP Client (Precision Time Protocol) for clock synchronization

\* SFP = Small Form-Factor Pluggable Module

Multimode fiber needs to meet or exceed fiber standard ITU-T G.651.

Single mode fiber needs to meet or exceed fiber standard ITU-T G.652

## SPECIFICATIONS

### Ethernet Ports

RJ-45 Ports:	(24) 10/100/1000Base-TX, with Auto MDI/MDIX & PoE
SFP Ports:	(4) 1000Base-FX

### Ethernet Standards Supported

IEEE 802.3 for 10Base-T  
 IEEE 802.3u for 100Base-TX and 100Base-FX  
 IEEE 802.3z for 1000Base-X  
 IEEE 802.3ab for 1000Base-T  
 IEEE 802.3at for Power Sourcing Equipment (PSE) and PoE (up to 30 watts per port)  
 IEEE 802.3x for Flow control  
 IEEE 802.3ad for LACP (Link Aggregation Control Protocol)  
 IEEE 802.1D for STP (Spanning Tree Protocol)  
 IEEE 802.1p for COS (Class of Service)  
 IEEE 802.1Q for VLAN Tagging  
 IEEE 802.1w for RSTP (Rapid Spanning Tree Protocol)  
 IEEE 802.1s for MSTP (Multiple Spanning Tree Protocol)  
 IEEE 802.1x for Authentication  
 IEEE 802.1AB for LLDP (Link Layer Discovery Protocol)

### Switch Properties

Switching Latency:	7 $\mu$ s
Switching Bandwidth:	56 Gbps
Max. Number of VLANs Available:	256
IGMP Multicast Groups:	128 for each VLAN
Port Rate Limiting:	User Defined
MAC Table:	8000 MAC addresses available
Priority Queues:	4
Processing:	Store-and-Forward
Jumbo Frame:	Up to 9000 Bytes

### Security Features

Device Binding Security  
 Enable/Disable Ports, MAC based port security  
 Port-Based Network Access Control: 802.1x  
 VLAN (802.1Q): To segregate and secure network traffic  
 Radius Centralized Password Management  
 SNMPv3 Encrypted Authentication and Access Security  
 SSH  
 TACACS+

### Software Features

STP/RSTP/MSTP (IEEE 802.1D/w/s)  
 C-Ring Redundant Ring: Recovery time <30ms, with over 250 switches within ring network  
 TOS/Diffserv Supported  
 Quality of Service (802.1p) for Real-Time Traffic  
 VLAN (802.1Q) with VLAN Tagging and GVRP Supported  
 IGMP Snooping for Multicast Filtering  
 Port Configuration, Status, Statistics, Monitoring, & Security  
 DHCP Server / Client support  
 IP-Based Bandwidth Management  
 Application-Based QoS Management  
 DOS/DDOS Auto Prevention

### Network Redundancy

C-Ring  
 Legacy Ring  
 RSTP  
 STP  
 MSTP

### Alarms & Monitoring Systems

Relay Output:	For fault event alarming
Syslog Server / Client:	To record and view events
SMTP:	For event warning notifications via email
Event Selection Support	
RS-232 Serial Console DB-9 Port:	RS-232 @ 115,200 bps, with console cable (included).

### LED Status Indicators

Power Indicators:	For AC operating power
System Ready Indicator:	Indicates switch is in the "ready" mode, or switch is upgrading firmware
Ring Master Indicator:	Indicates switch is operating in the C-Ring Master mode
C-Ring Indicator (Ring):	Indicates switch is operating in the C-Ring mode. A flashing LED in this mode indicates the network ring has broken or faulty.
System Running Indicator:	Switch is operating continuously
Supervisor Log-In Indicator:	Switch is being accessed remotely
Reset to Default Running Indicator (DEF):	Switch is reset to the default configuration
Ping Command to the Switch Indicator:	Switch is processing a Ping request
PoE Indicator:	PSE (Power Sourcing Equipment) power output
10/100/1000BASE-TX	
RJ-45 Port Indicator:	Bi-color LED indicates 1000 Mbps or 10/100 Mbps port/link activity
1000BASE-FX SFP Port Indicator:	Port/link activity

**SPECIFICATIONS**

**Regulatory Approvals**

EMI:	FCC Part 15, CISPR (EN55022) Class A
EMS:	EN61000-4-2
ESD:	EN61000-4-3
RS:	EN61000-4-4
(EFT:	EN61000-4-5
Electrical Surge:	EN61000-4-6
CS:	EN61000-4-8, EN61000-4-11
Mechanical Shock:	IEC60068-2-27
Free Fall:	IEC60068-2-32
Vibration:	IEC60068-2-6

**Electrical & Mechanical**

AC Input:	100 to 240 VAC, 50-60 Hz.
AC Power Consumption, Typical:	36 Watts. 720 watts with 24 ports loaded with PoE+, at a maximum ambient operating temperature of +50° C. De-rate to any combination of PoE or PoE+ at a maximum PD demand of 400 watts total with 24 ports loaded, at a maximum ambient operating temperature of 75° C.
Current Protection:	Overload Current Protected
Enclosure:	1-RU high, 19-inch rack-mountable
Size (in./cm) (L×W×H)	13.46 × 16.97 × 1.73 in. (34.2 × 43.1 × 4.4 cm)
Shipping Weight:	<13 lbs./6 kg

**Environmental**

MTBF:	>100,000 hours
Operating Temp:	-40° to +75° C (-40° to +167° F) Functional to +85° C
Storage Temp:	-40° to +85° C (-40 to 185°F)
Relative Humidity:	5% to 95% (non-condensing)*
Compliance:	Fully compliant with the environmental requirements (ambient operating temperature, storage temperature, mechanical shock, vibration, humidity with condensation, high-line/low-line voltage conditions, and voltage transient protection) of NEMA TS-1/TS-2 and the Caltrans specification for Traffic Signal Control Equipment.



\* May be extended to humidity with condensation conditions by adding suffix '/C'

**ORDERING INFORMATION**

Part Number	Description
CNGE28FX4TX24MSPOE+	(24) 10/100/1000 BASE-TX + (4) 1000BASE-FX Managed Switch with Power over Ethernet (PoE)
Options/Accessories	Add suffix '/C' for Conformally Coated Circuit Boards (Extra charge, consult factory) Rack-mount installation kit (Included) Console cable (Included) AC Power cable (Included)

NOTE: This product requires a fiber installation with a minimum 30 dB connector return loss. The use of Super Polish Connectors is recommended. Complies with FDA Performance Standard for Laser Products, Title 21, Code of Federal Regulations, Subchapter J. In a continuing effort to improve and advance technology, product specifications are subject to change without notice.



3 CORPORATE DRIVE | DANBURY, CT 06810 | USA  
 T: 203.796.5300 | F: 203.796.5303 | TECH SUPPORT: 1.888.678.9427 | INFO@COMNET.NET  
 8 TURNBERRY PARK ROAD | GILDERSOME | MORLEY | LEEDS, UK LS27 7LE  
 T: +44 (0)113 307 6400 | F: +44 (0)113 253 7462 | INFO-EUROPE@COMNET.NET