

DH-NVR7208/7216/7232/7264

8/16/32/64 Channel 1U Network Video Recorder



Features

- > Up to 8/16/32/64 channel IP camera input
- > H.264/MJPEG dual codec decoding
- > Max 256Mbps incoming bandwidth
- > HDMI / VGA simultaneous video output
- > 8/16/32channel synchronous realtime preview, GRID interface
- > Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek and etc.
- > ONVIF Version 2.3 conformance
- > 3D intelligent positioning with Dahua PTZ camera
- > Support 2 SATA HDDs up to 8TB, 2 USB2.0
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

DH-NVR7208/7216/7232/7264


Technical Specifications

| Model | DH-NVR7208 | DH-NVR7216 | DH-NVR7232 | DH-NVR7264 |
|------------------------------------|---|------------|------------------|------------------|
| System | | | | |
| Main Processor | Dual-core embedded processor | | | |
| Operating System | Embedded LINUX | | | |
| Video & Audio | | | | |
| IP Camera Input | 8 channel | 16 channel | 32 channel | 64 channel |
| Two-way Talk | 1 channel Input, 1 channel Output, RCA | | | |
| Display | | | | |
| Interface | 1 HDMI, 1 VGA | | | |
| Resolution | 1920×1080, 1280×1024, 1280×720, 1024×768 | | | |
| Display Split | 1/4/8/9 | 1/4/8/9/16 | 1/4/8/9/16/25/36 | 1/4/8/9/16/25/36 |
| OSD | Camera title, Time, Video loss, Camera lock, Motion detection, Recording | | | |
| Recording | | | | |
| Compression | H.264 / MJPEG | | | |
| Resolution | 5Mp(2560×1920)/3Mp(2048×1536)/1080P(1920×1080)/720P(1280×720)/D1(704×576/704×480) & etc. | | | |
| Record Rate | 192Mbps | | | |
| Bit Rate | 48~ 8192kbps | | | |
| Record Mode | Manual, Schedule(Regular(Continuous), MD, Alarm), Stop | | | |
| Record Interval | 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec | | | |
| Video Detection & Alarm | | | | |
| Trigger Events | Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips | | | |
| Video Detection | Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank | | | |
| Alarm Input | 8 channel | 8 channel | 8 channel | 8 channel |
| Relay Output | 3 channel | 3 channel | 3 channel | 3 channel |
| Playback & Backup | | | | |
| Sync Playback | 1/4/9 | 1/4/9/16 | 1/4/9/16 | 1/4/9/16 |
| Search Mode | Time/Date, Alarm, MD & Exact search (accurate to second), Smart search | | | |
| Playback Function | Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom | | | |
| Backup Mode | USB Device / Internal SATA burner/ Network | | | |
| Network | | | | |
| Ethernet | 1 RJ-45 port (10/100/1000Mbps) | | | |
| Network Function | HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS and | | | |

DH-NVR7208/7216/7232/7264

| | |
|----------------------------|---|
| | etc.) |
| Max. User Access | 128 users |
| Smart Phone | iPhone, iPad, Android, Windows Phone |
| Storage | |
| Internal HDD | 2 SATA ports up to 8TB |
| Auxiliary Interface | |
| USB | 2 ports (1 Rear), USB2.0 |
| RS232 | 1 port, For PC communication & Keyboard |
| RS485 | 1 port, For PTZ control |
| General | |
| Power Supply | DC 12V/5A |
| Power Consumption | 60W (without HDD) |
| Working Environment | -10°C~+55°C / 10%~90%RH / 86~106kpa |
| Dimension (W×D×H) | 1U, 375mm×285mm×50mm |
| Weight | 2.3KG (without HDD) |

System Connection



* Take NVR7232 as an example

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuasecurity.com

*Design and specifications are subject to change without notice.

DH-NVR7208/7216/7232/7264
