

## DH-SD6581B/81C-HN

---

### 1.3Mp HD Network PTZ Dome Camera



#### Features

- 28x / 30x optical zoom
- H.264 & MJPEG dual-stream encoding
- Max. 25/30fps @1.3M(1280×960) & 720P resolution
- WDR, Day/Night(ICR), DNR (2D&3D),Auto iris, Auto focus, AWB, AGC,BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- Max 400°/s pan speed, 360° endless pan rotation
- Up to 255 presets, 5 auto scan, 8 tour, 5 pattern
- Built-in 7/2 alarm in/out
- Support intelligent 3D positioning with DH-SD protocol
- Micro SD memory, IP67, easy installation

# DH-SD6581B/81C-HN

## Technical Specifications


Model	DH-SD6581B-HN	DH-SD6581C-HN
<b>Camera</b>		
Image Sensor	1/4" CMOS	1/3" CCD
Effective Pixels	1280(H) x 960(V)	
Scanning System	Progressive	
Electronic Shutter Speed	PAL/ NTSC: 1/1~1/10000s	PAL:1/3~1/10000s NTSC:1/4~1/10000s
Min. Illumination	Color:0.25Lux/F1.35 B/W: 0.03Lux/F1.35	Color:0.1Lux B/W:0.005Lux
S/N Ratio	More than 50dB	
Video Output	BNC(1.0Vp-p/75Ω), PAL / NTSC	
<b>Camera Features</b>		
Day/Night	Auto(ICR) / Color / B/W	
Backlight Compensation	BLC / HLC / WDR	
White Balance	Auto, ATW, Indoor, Outdoor, Manual	
Gain Control	Auto / Manual	
Noise Reduction	2D / 3D	
Privacy Masking	Up to 24 areas	
Defog	N/A	On/Off
Digital Zoom	12x	2x
<b>Lens</b>		
Focal Length	3.5mm~98.0mm (28x Optical zoom)	4.4mm~132mm (30x Optical zoom)
Max Aperture	F1.35 ~ F3.7	F1.4~ F4.6
Focus Control	Auto / Manual	
Angle of View	H: 55.9°~2.1°	H: 30.5°~ 1.82°
Close Focus Distance	10mm(wide) ~ 1500mm(Tele)	N/A
<b>PTZ</b>		
Pan/Tilt Range	Pan: 0° ~ 360° endless; Tilt: -2° ~ 90°, auto flip 180°	
Manual Control Speed	Pan: 0.1° ~ 300°/s; Tilt: 0.1° ~ 250°/s	
Preset Speed	Pan: 400°/s; Tilt: 300°/s	
Preset	80(DH-SD), 255(Pelco-P/D)	
PTZ Mode	5 Pattern, 8 Tour, Auto Pan, Auto Scan	
Speed Setup	Human-oriented focal length/ speed adaptation	
Power up Action	Auto restore to previous PTZ and lens status after power failure	
Idle Motion	Activate Preset/Pan/Scan/Tour/Pattern if there is no command in the specified period	
Time Task	Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time	
Protocol	DH-SD, Pelco-P/D (Auto recognition)	
<b>Video</b>		
Compression	H.264 / MJPEG	
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480) /	

## DH-SD6581B/81C-HN

		CIF(352×288/352×240)	
Frame Rate	Main Stream	1.3M(1~ 25/30fps), 720P(1 ~ 25/30fps)	720P(1 ~ 25/30fps)
	Sub Stream	D1/CIF(1 ~ 25/30fps)	
Bit Rate		H.264: 56K ~ 8192Kbps, MJPEG: 56K ~ 20480Kbps	
<b>Audio</b>			
Compression		G.711a / G.711u(32kbps) / PCM(128kbps)	
Interface		1/1 channel In/Out	
<b>Network</b>			
Ethernet		RJ-45 (10/100Base-T)	
Protocol		IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	
ONVIF		ONVIF Ver. 2.0 conformance	
Max. User Access		20 users	
Smart Phone		iPhone, iPad, Android, Windows Phone	
<b>Auxiliary Interface</b>			
Memory Slot		Micro SD, Max 32GB	
RS485		1	
Alarm		7/2 channel In/Out	
<b>General</b>			
Power Supply		AC 24V/3A (±10%) / DC12V optional	
Power Consumption		15W, 40W(Heater on)	
Working Environment		-40°C ~ 60°C / Less than 90% RH	
Protection Level		IP67, IK10 optional	
Dimensions		Φ222(mm) x 322 (mm)	
Weight		5.0kg	

# DH-SD6581B/81C-HN

## Dimensions (mm)



## Accessories

		
DH-69FB	DH-PFA111	Power Supply

## DH-SD6581B/81C-HN

### Accessories (Optional)

			
DH-PFB300C	DH- PFB301C	DH-PFA112	DH-PFA113
			
DH-PFB301S	DH-PFA120	DH-PFA150	DH-PFA151

---

#### Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

\*Design and specifications are subject to change without notice.

© 2013 Dahua Technology Co., Ltd.