



DLR4-08/1.5TBD

Article-No.: 73194

Digital Video Recorder (8 Channels), 1.5 TB, H.264, 200fps, 704x576, DVD, Audio

Mainfeatures

Pentaplex operation
Recording speed: 200 ips max.
8 loop-through inputs / VGA, composite outputs
2-way audio / alarm inputs & outputs
Live picture & playback zoom (4x)

H.264 video compression standard
Video resolution: 704x576 px. max.
Network connectivity (10/100Base-T Ethernet)
Storage capacity: 1500GByte (3 HDDs max.)
Browser access & RASPlus/RAS mobile remote control

Specifications

Series	eneo DLR
Operation mode	Pentaplex
Operation Mode	Live, Playback, Record, Network, Backup
Video standard	PAL/NTSC (automatic selection)
Video inputs (amount)	8
Video inputs	1Vp-p, (C)VBS, 75ohms, BNC (loop-through)
Main exits	VGA, composite (CVBS)
Video outputs	1Vp-p, 75ohms, BNC
Spot monitor	composite (CVBS)
IP channels	-
Audio inputs	4
Audio output	1x line-out, Cinch
Alarm inputs	8x TTL, programmable as NC/NO
Motion detector	32x24 (768) grid per camera, Sensitivity levels: 5. Minimum size for detection: 256 levels. Video signal obscuration and video signal blind detection.
Alarm recording	event, pre- and post alarm, panic and video loss
Covert Camera Recording	available





Specifications (continued)

Alarm out	On system and disk fail
Acoustic alarm display	ON/OFF switchable
Alarm outputs	2x NO/NC contact
Alarm notification	e-mail, remote software (RASplus), callback
Alarm reset input	TTL input
Event Logs	No limit for alarm-in, motion, video loss, text-in
System logs	Up to 5,000 for user login/out, config. changes, remote access, connects/disconnects and errors, disk read and write errors
Max. recording resolution	704 x 576
Resolution	720x576 Pixels (Display)
Compression standard	H.264
Compression standard	(H.264: advanced compression engine provides smaller data size without significant picture quality distortion)
Image size	Low: 2/2.4kB, Standard: 4/4.8kB, High: 6/7.2kB, Very high: 8/9.6kB (NTSC/PAL), at CIF resolution
Max. recording rate	200 B./Sek.
Max. recording rate	@ 352 x 288
Recording speed	200 ips. at CIF (352x288 Px.), 100 ips. at 2CIF (704x288 Px.), 50 ips. at 4CIF (704x576 Px.) / PAL
Digital storage media	SATA hard disk
Harddisk capacity (internal)	1,5 TB
Max. harddisk capacity (internal)	6 TB
Recording modes	Continuous, Time-lapse, Motion Detection, Text-in, Pre-alarm, Panic
Digital signature	watermark
Pre-alarm recording	up to 30min.
Post-alarm recording	up to 15min.
Playback	full screen, 4 channel split, 8 channel split, PiP
Playback speed	200 ips. at CIF (352x288 Px.), 100 ips. at 2CIF (704x288 Px.), 50 ips. at D1 (704x576 Px.) / PAL
Monitor display	real time: 25 ips (PAL), 30 ips (NTSC) per camera
Zoom function	2x-4x
Search function	Date/Time, Record table, Calendar, Event, Motion, Museum, Text-In
Intergrated writer	DVD
Secondary Storage	via USB 2.0: HDD, Flash drive, built-in SATA DVD RW. Network Data Export: Clip Player, AVI, JPG, BMP
Control units (external)	system keyboard, mouse
Remote control	included
Remote access	browser, remote software
Remote Software	For remote administration and search function (RASplus, Webguard, supplied with the unit)
Scheduling	Different schedule for 7 days per week, programmable holidays, hour-by-hour configuration, time-lapse, event-driven, 2 mixed independent time-lapse schedules
Menu languages	German, English, French, Italian, Spanish, Dutch, Danish, Polish, Russian, Czech, Hungarian
Network	10/100 Base-Tx, RJ45
Network protocols	TCP/IP, DHCP, SMTP, PPPoE

Specifications (continued)

Transmission rate (Network)	100 ips (CIF), 50 ips (2CIF), PAL
Interfaces external storage	USB
Interfaces external storage	2x USB 2.0
Serial interfaces	RS-485, RS-232
Serial interfaces	RS-485 for telemetry control (proved protocols: eneo-Fastrax, Pelco P&D) or remote keyboard control
Text insertion interface	ATM/POS, 10 chann. max.
Password protection	64 groups, 256 users
Supply voltage	100VAC ~ 240VAC, 0.6A 50/60Hz
Power consumption	40W
Temperature range (operation)	+5°C ~ +40°C
Housing	Steel metal with plastic front, desktop design
Colour	Pantone 427C
Dimensions (HxWxD)	88x430x405mm
Weight	6.8kg
Parts supplied	IR Remote control unit, 19" Rack mount kit, Power supply unit 100~240VAC / 2A with Mains cable, Viewer CD ROM (RASplus), Manuals
Certificates	CE

Optional Accessories

Image	Artikel-Nr. / Typ	Description
	EDC-KBDM-3	System Keyboard w. Joystick, 5" Monitor 12VDC, Fastrax Protocol
	EDC-KBD1	System Keyboard with 3-axis Joystick, 12VDC
	KBD-2	System Keyboard with 3-Axis Joystick and Jog Shuttle, 12VDC
	KBD-NSC-100	Network System Controller with 3-Axis Joystick and Jog Shuttle, 5VDC

Optional Accessories (continued)

Image	Artikel-Nr. / Typ	Description
	DVR-MOUSE	USB Mouse for Recorder Series DTR, DPR, BLR and DLR3/4 - PS/2, USB
	USB-8COM	Serial Text Interface Converter 8x RS232 for DLR-/DTR -/DPR-/DMR-series
	HDD-500SATA-W	Hard Disk Drive 500GB, SATA for EMD-19/ DVR-S1, BCR series
	HDD-1000SATA-H2	Hard Disk Drive 1TB, SATA for eneo BLR, DLR, DMR Series
	RAS+	Remote Administration Interface Software for DLR, DMR, DTR, DCR, DPR, DIR DVRs
	RAS MOBILE	PDA Remote Monitoring Software for DLR, DMR, DCR, DTR, DPR Recorders
	HDD-500SATA-H	Hard Disk Drive 500GB, SATA, for eneo BLR, DLR, DMR Series



Your partner for eneo products:

