



Covert & Fixed Dome Cameras

FDP-No.: 91813

VKC-149/PIR

- For Wall Mount
- Resolution of 380 Horizontal Lines
- Built-in Pinhole Lens F2.0/3.7 mm
- Electronic Shutter Control (ESC)
- Internal Synchronization
- Easy Installation
- Supply Voltage: 12 VDC



Specifications:

Imager	1/4" Interline transfer CCD
System	CCIR/PAL
Synchronization	Internal
Sensitivity at 50% videosignal	2.5 Lux at F2.0 (VT measurement result)
Horizontal resolution	380 TV lines
Picture elements	Approx. 290,000 (H) 512 x (V) 582
Signal-to-noise ratio	>45 dB (AGC OFF)
Linear shutter (ESC)	1/50 to 1/100,000 sec. (automatic)
Video output	1 Vp-p, CCVS, 75 Ohm
Lens	F2.0/3.7 mm Pinhole
Horizontal angle of view	Approx. 55°
Supply voltage	12 VDC +/-10 %
Power consumption	Approx. 1.3 W
Mounting	Wall mount (bracket included)
Temperature range	-10° to +50°C
Housing	Plastic
Colour	Light grey
Dimensions (HxDxW)	110x70x50 mm(w./o. bracket)
Weight	Approx. 100 g

Accessories	
EDP No. / Type	Description
70443 VT-PS12DC-4	Power supply unit 230 VAC/12 VDC stabilized with DC plug
77779 VT-PS12DC/UK	Power supply unit 230VAC/12VDC-500mA w. UK mains connector

e-mail: info@eneo-security.com • www.eneo-security.com