

Camera housings

FH 7154 H – outdoor housing HEM with sunshield and heater

Outer dimensions: 105 (W) x 95 (H) x 355 (L) mm
Inner dimensions: 70 (W) x 65 (H) x 300 (L) mm
Dimensions sunshield: 113 (W) x 71 (H) x 410 (L) mm
Material: extruded and die-cast aluminium
Colour: powder-coated RAL 9002
Weatherproof rating: IP 66
Operating temperature: -20°C ~ +50°C
Heater: thermostat controlled, 115 ~ 240 V AC, 40 W
Weight: 1,9 kg



FH 7156 H – outdoor housing HEB with sunshield and heater

Outer dimensions: 137 (W) x 107 (H) x 387 (L) mm
Inner dimensions: 84 (W) x 73 (H) x 320 (L) mm
Dimensions sunshield: 144 (W) x 100 (H) x 440 (L) mm
Material: extruded and die-cast aluminium
Colour: powder-coated RAL 9002
Weatherproof rating: IP 66
Operating temperature: -20°C ~ +50°C
Heater: thermostat controlled, 115 ~ 240 V AC, 40 W
Weight: 3,3 kg



FH 7157 H – outdoor housing HEC with cable channel, sunshield and heater

Outer dimensions: 137 (W) x 107 (H) x 387 (L) mm
Inner dimensions: 84 (W) x 73 (H) x 320 (L) mm
Dimensions sunshield: 144 (W) x 100 (H) x 440 (L) mm
Material: extruded and die-cast aluminium
Colour: powder-coated RAL 9002
Weatherproof rating: IP 66
Operating temperature: -20°C ~ +50°C
Heater: thermostat controlled, 115 ~ 240 V AC, 40 W
Weight: 3,3 kg

