



PT-SERIES

FLIR PT-SERIES

High Performance Pan/Tilt Multi-Sensor Thermal Cameras

FLIR's PT-Series brings thermal and visible-light imaging together in a system that gives you video and control over both IP and analog networks.

The PT-Series' precision pan/tilt mechanism gives you accurate pointing control while providing fully programmable scan patterns, radar slew-to-cue, and slew-to-alarm functions. PT-Series cameras define a new standard of performance with five models that provide full 640 x 480 thermal resolution with full WDR Thermal video.

Designed for high performance, easy installation, and long-term reliability, PT-Series cameras give you the image detail needed for optimal threat detection capability and peak analytics performance - even in challenging imaging environments.

Because FLIR understands that you need cameras for the real world, PT-Series cameras are qualified beyond industry standard for survivability, and are backed by FLIR's unparalleled 2-year system warranty and 10-year detector warranty.



Crisp image detail gives you optimum clarity to identify and address any number of security threats

KEY FEATURES

- Simultaneous IP and analog video outputs – thermal and visible-light – along with IP and serial control interfaces for easy integration into IP or analog networks; use them in an existing analog environment, and migrate easily to a future IP network
- Sun-safe VOx uncooled thermal sensor technology; looking directly at the sun won't damage FLIR uncooled thermal security cameras
- Exchangeable camera cassettes allow for quick upgrade or repair of sensors and optics
- All 640 x 480 resolution products are based on FLIR's 17-micron pixel pitch arrays, the most advanced uncooled detectors available on the commercial market
- Open IP standards for plug-and-play integration; ONVIF compliant
- Multiple simultaneous channels of streaming digital video available in H.264, MPEG-4, or M-JPEG formats

Specifications

Camera Model PT-Series			
Camera Platform Type	PTZ Multi-Sensor	PTZ Multi-Sensor	PTZ Multi-Sensor
Thermal Camera Specs			
Array Format (NTSC)	160 × 120	320 × 240	640 × 480
Detector Type	Long-Life, Uncooled VO× Microbolometer	Long-Life, Uncooled VO× Microbolometer	Long-Life, Uncooled VO× Microbolometer
Effective Resolution	19,200	76,800	307,200
Pixel Pitch	25 μm	25 μm	17 μm
Field Of View	24° × 20° (PT-124; 9 mm) 17° × 14° (PT-117; 13 mm) 12° × 10° (PT-112; 19 mm)	48° × 39° (PT-348; 9 mm) 34° × 28° (PT-334; 13 mm) 24° × 19° (PT-324; 19 mm) 13° × 10° (PT-313; 35 mm) 7° × 5° (PT-307; 65 mm) 4.6° × 3.7° (PT-304; 100 mm)	45° × 37° (PT-645; 13 mm) 25° × 20° (PT-625; 25 mm) 18° × 14° (PT-618; 35 mm) 12° × 10° (PT-612; 50 mm) 10° × 8° (PT-610; 65 mm) 6.2° × 5° (PT-606; 100 mm)
Zoom	2× E-zoom	2× & 4× E-zoom	2× & 4× E-zoom
Spectral Range	7.5 μm to 13.5 μm	7.5 μm to 13.5 μm	7.5 μm to 13.5 μm
Focus Range	athermalized, focus-free	athermalized, focus-free	athermalized, focus-free
Outputs			
Composite Video NTSC or PAL	Standard	Standard	Standard
Video over Ethernet	Two independent channels of streaming MPEG-4, H.264, or M-JPEG for each of two cameras	Two independent channels of streaming MPEG-4, H.264, or M-JPEG for each of two cameras	Two independent channels of streaming MPEG-4, H.264, or M-JPEG for each of two cameras
Control			
Point to point (stand alone)	Yes	Yes	Yes
Ethernet	Yes	Yes	Yes
Serial	RS-232/-422; Pelco D, Bosch	RS-232/-422; Pelco D, Bosch	RS-232/-422; Pelco D, Bosch
Network Enabled	Yes	Yes	Yes
Software Developer's Kit	Option	Option	Option
External Analytics Compatible	Yes	Yes	Yes
Pan/Tilt Performance			
Pan Angle/Speed	Continuous 360°; 0.1° to 60°/sec	Continuous 360°; 0.1° to 60°/sec	Continuous 360°; 0.1° to 70°/sec
Tilt Angle/Speed	+90° to -90°; 0.1° to 30°/sec	+90° to -90°; 0.1° to 30°/sec	+90° to -90°; 0.1° to 30°/sec
Programmable presets	128	128	128
General			
Weight	~37 lb (configuration dependent)	~37 lb (configuration dependent)	~37 lb (configuration dependent)
Dimensions (L,W,H)	13.7" × 18.4" × 12.8" (348 mm × 467 mm × 326 mm)	13.7" × 18.4" × 12.8" (348 mm × 467 mm × 326 mm)	13.7" × 18.4" × 12.8" (348 mm × 467 mm × 326 mm)
Input Voltage	24 VAC (21-30 VAC) 24 VDC (21-30 VDC)	24 VAC (21-30 VAC) 24 VDC (21-30 VDC)	24 VAC (21-30 VAC) 24 VDC (21-30 VDC)
Power Consumption (Consult product manuals for details of power requirements)	24 VAC: 85 VA (max w/o heaters) 215 VA (max w/heaters) 24 VDC: 65 W (max w/o heaters) 195 W (max w/heaters)	24 VAC: 85 VA (max w/o heaters) 215 VA (max w/heaters) 24 VDC: 65 W (max w/o heaters) 195 W (max w/heaters)	24 VAC: 85 VA (max w/o heaters) 215 VA (max w/heaters) 24 VDC: 65 W (max w/o heaters) 195 W (max w/heaters)
Visible Light Camera			
	Sony FCB-EX1010	Sony FCB-EX1010	Sony FCB-EX1010
Sensor Type	1/4" Exview HAD CCD		
Lens Field of View	57.8° (h) to 1.7° (h)		
Focal Length	3.4 mm to 122.4 mm		
Zoom	36× Optical zoom, 12× E-zoom		
F/#	1.6 to 4.5		
Effective pixels (NTSC)	380,000	380,000	380,000

SANTA BARBARA

FLIR Systems, Inc.
70 Castilian Drive
Goleta, CA 93117
USA
PH: +1 805.690.5097

PORTLAND

Corporate Headquarters
FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
USA
PH: +1 866.477.3687

BELGIUM

FLIR Systems
Luxemburgstraat 2
2321 Meer
Belgium
PH: +32 (0) 3665 5100

CHINA - SHANGHAI

FLIR Systems, Co., Ltd.
K301-302, No.26 Lane
168, Daduhe Road,
Putuo District, Shanghai
200062, P.R.China
PH: +86-21-5169 7628

www.flir.com
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2014 FLIR Systems, Inc. All rights reserved. (Updated 12/03/14)