

ZC-DT4000 VANDAL-RESISTANT DOME SERIES

Super High Resolution Vandal-resistant Domes



- Super high resolution
- Integrated 3.0-9.0mm varifocal lens
- Weatherproof (IP66 rated)
- Impact- and scratch-resistant polycarbonate bubble
- Simple camera set-up via OSD
- Backlight compensation
- Easy adjustment with the unique 3-axis gimble

The new ZC-D4000 range includes the ZC-DT4039PHA vandal-resistant dome camera for harsh environment surveillance solutions. The dome bubble is constructed from extra strong impact resistant polycarbonate, and a vandal-resistant IP66-rated housing with anti-tamper Torx screws is supplied.

The ZC-DNT4039PHA is a true day/night unit with a 3.0-9.0mm varifocal lens to provide clear, sharp images in all circumstances. The ZC-DWT4039PHA dome combines vandal-resistant features with a super wide dynamic camera using next-generation Pixim-based technology. This allows the camera to capture detail in shadows and manage light more effectively in bright glare.

Perfect Partners



ZM-L217(E)
Page 65



C-MP404DVR
Page 56

Model	ZC-DT4039PHA	ZC-DNT4039PHA	ZC-DWT4039PHA
TV System	PAL	PAL	PAL
Focal Length	3.0-9.0 mm	3.0-9.0 mm	3.0-9.0 mm
Max Aperture Ratio	1:1.3	1:1.3	1:1.3
Angle of View: horizontal	90.0° ~ 31.8°	90.3° ~ 31.9°	90.0° ~ 31.8°
Resolution (Horizontal)	540 TVL	540 TVL	520 TVL
Minimum Illumination (100 IRE)	1.0 lux	1.0 lux (Day)/ 0.08 lux (Night)	1.3 lux
Digital Day/Night	SDN Auto/On/Off	N/A	SDN Auto/On/Off
Power Supply	12V DC/24V AC	12V DC/24V AC	12V DC/24V AC
Power Consumption	4W	4.3W	3W
IP Rating	IP66	IP66	IP66
External Dimensions	171(D)mm x 100 (H)mm	171(D)mm x 100 (H)mm	171(D)mm x 100 (H)mm
Weight (approximate)	586g	586g	586g

Ordering Codes:

ZC-DT4039PHA 540TVL Vandal-resistant Colour Dome

ZC-DNT4039PHA 540TVL True Day/Night Colour/Mono Vandal-resistant Dome

ZC-DWT4039PHA Wide Dynamic Range 520 TVL

Colour Camera





ZC D4000 & ZC D5000 RANGE OF ACCESSORIES

Internal & External Dome Accessories

Cameras

ZC D4000 RANGE

Internal

<p>Internal gooseneck arrangement Ordering Codes: ZCA-GN400W ZCA-DMA400W Wall-mounted Gooseneck bracket and Adaptor</p> 	<p>Internal flush mount Ordering Codes: ZCA-FMA400W</p> 
<p>Internal corner mount Ordering Codes: ZCA-CMA400W</p> 	<p>Internal pendant mount Ordering Codes: ZCA-DMA400W (pole not included)</p> 
<p>Test lead Ordering Codes: ZCA-SM400</p> 	<p>Internal quick install pipe Ordering Codes: ZCA-QIP</p> 

External

<p>External pendant mount Ordering Codes: ZCA-DMA400W-T (pole not included)</p> 	<p>External gooseneck arrangement Ordering Codes: ZCA-GN400W ZCA-DMA400W-T Wall-mounted Gooseneck bracket and adaptor</p> 
--	--

ZC D5000 RANGE

Internal

<p>Internal gooseneck arrangement Ordering Codes: ZC5-WM1 Wall-mounted gooseneck bracket</p> 	<p>Internal pendant mount Ordering Codes: ZC5-PM1 (pole not included)</p> 
---	--

External

<p>External gooseneck arrangement Ordering Codes: ZC5-WM2 Wall-mounted gooseneck bracket</p> 	<p>External pendant mount Ordering Codes: ZC5-PM2 (pole not included)</p> 
<p>External vandal-resistant dome housing Ordering Codes: ZC-OH5</p> 	

Lenses

Cameras

Hardware

Control Room

IP Media & Transmission

Radar Detection

ANPR

Accessories