

TECHNICAL DATA SHEET

GTP002S

Passive Baluns



KEY FEATURES

Genie's "Smart Cabling" passive Baluns are designed for use with Category 5e Unshielded Twisted Pair (UTP) cable. UTP cable is more flexible than traditional coaxial cable, is lower cost and has better transmission qualities. Passive baluns do not require any power source and match the 75 Ω impedance of coaxial cable to the 100 Ω impedance of UTP cable. Passive Baluns can transmit and receive full motion composite video signals up to 300 metres in Colour and 600 metres in Monochrome.

- Impedance Matching 75 Ω Coaxial to 100 Ω Twisted Pair
- Transmits/receives Composite Video Signals
- Transmits Distances – 300m in Colour, 600m in Monochrome
- Ultra-low Profile Design 60mm(l) x 19mm(h) x 15mm(w)
- Ideal for Multiple Connections on DVR's & Multiplexers
- BNC Male to Terminal Block Connections
- For use with Category 5, 5e & 6 UTP (Unshielded Twisted Pair) Cable. Wire Gauge 24awg
- Uses One Twisted Pair for a Single Composite Video Signal
- No External Power Required

TECHNICAL DATA SHEET

TECHNICAL SPECIFICATION

Model Number	GTP002S
Dimension (Wx H x D)	60 x 19 x 15mm

Features and specification are subject to change for further improvement without any notice.