

# Series SN-44

## Pan/tilt heads



### Product information

Pan/tilt head, 24 VAC, for outdoor use  
remote indication potentiometer for  
prepositionin

- | High load capacity
- | Varying speeds
- | 24 VDC motors
- | Low drive clearance
- | Robust, mechanical construction
- | Aluminium-cast housing
- | Externally adjustable maximum angle
- | IP-66 protection rating
- | Top and side platform mounting  
included in shipment

## Technical data

	<b>SN-44/24DC PT</b>
Maximum load	20 kg
Rated voltage/operating voltage	24 VDC
Power consumption	36 VA
Maximum panning angle	5° to 350°
Maximum tilting angle	+20° to -90°
Panning speed	48°/sec.
Tilting speed	16°/sec.
Drive clearance	0.5°
Suitable for fixed position	Yes
Automatic shut-off	Adjustable from exterior
Operating temperature range	-20 °C to +55 °C
Protection rating	IP-66
Mounting position	Standing
Finish	RAL 7032 (pebble grey)
Weight	Approx. 7.5 kg
Compatible operating console	MBeg-422; MBeg/VS
<b>Order No.</b>	<b>5.20550</b>

### Mounting accessories

Description	Wall console for pan/tilt heads from Series 40	Mast console for pan/tilt heads from Series 40	Mast adapter for Series 40
Type	WK/SN	MK/SN	MA/SN
Overhang	345 mm	350 mm	-
Total length	415 mm	420 mm	-
Tilting range	Up: 65°; down: 50°	Up: 65°; down: 50°	-
Max. load	Approx. 30	Approx. 25 kg	Approx. 30 kg
Dimensions	-	-	Ø 140 x 200 mm (H)
Weight	Approx. 2.3 kg	Approx. 3 kg	Approx. 2.3 kg
Finish	RAL 7032 (pebble grey)	RAL 7032 (pebble grey)	RAL 7032 (pebble grey)
<b>Order No.</b>	<b>5.18380</b>	<b>5.18390</b>	<b>5.18400</b>

Technical alterations reserved

**GEUTEBRÜCK GmbH**

Im Nassen 7-9 | D-53578 Windhagen | Tel. +49 (0)2645 137-0 | Fax-999 E-mail: info@geutebrueck.com | Web: [www.geutebrueck.de](http://www.geutebrueck.de)