


# DS-2CC11A1P(N)-VFIR


## 700 TVL Vari-focal IR Bullet Camera



### Key features

- 1/3" SONY CCD
- 700TVL Horizontal Resolution
- 2.8–12mm Vari-focal Lens
- True Day/Night
- OSD Menu, DNR, Smart IR, Eclipse
- 30m IR Distance
- IP66 Rating

### Dimensions



DS-2CC11A1P(N)-VFIR	
<b>Camera</b>	
Image Sensor	1/3" SONY CCD
Signal System	PAL/NTSC
Effective Pixels	PAL: 976 (H) × 582 (V) NTSC: 976 (H) × 494 (V)
Min. Illumination	0.001 Lux @ (F1.2, AGC ON), 0 Lux with IR 0.0014 Lux @ (F1.4, AGC ON), 0 Lux with IR
Shutter speed	PAL: 1/50 s to 1/100,000 s NTSC: 1/60 s to 1/100,000 s
Lens	2.8 - 12 mm @ F1.4 Angle of view: 80° - 27.2°
Lens Mount	φ14
Auto Iris	DC drive
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°
Day & Night	IR cut filter with auto switch
Horizontal Resolution	700 TVL
Synchronization	Internal/Power synchronization
Video Output	1Vp-p composite output (75 Ω/BNC); Test monitor out [1Vp-p composite output (75 Ω/BNC), device line]
S/N Ratio	More than 62 dB
<b>Menu</b>	
Camera ID	On/Off (52 letters, position adjustable)
D/N Mode	Auto /Day/Night/EXT1/EXT2
White Balance	ATW/PUSH/USER1/USER2/ANTI CR/MANUAL/PUSH LOCK
Privacy Masking	On/Off, maximum 8 zones
Motion Detection	On/Off
Back Light	BLC/HLC/Off
Language	Chinese/ English/ Japanese/ German/ French/ Russian/ Portuguese/ Spanish
Video	SMART IR, ATR, HLC, DNR, Sharpness, Brightness, Contrast, Hue, Gain, Mirror, Defect Pixel Correction
<b>General</b>	
Working Temperature/ Humidity	-10 °C - 60 °C (14 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	24 V AC ± 10%, 12 V DC ± 10%
Ingress Protection	IP66
IR Range	approx 20 to 30 meters
Power Consumption	Max. 9.5 W
Dimensions	96.9 x 84.2 x 315.4 mm (3.81" × 3.31" × 12.42")
Weight	2100 g (4.62 lbs)

### Available models

PAL: DS-2CC11A1P- VFIR  
NTSC: DS-2CC11A1N- VFIR