


DS-8008/8012HMF Series Mobile DVR



Key Features

- Each channel supports up to 4CIF real-time encoding
- Dual stream
- Anti-shock technology
- 2x2.5" pluggable SATA HDD/SSD
- Support redundant mirror recording and master-slave recording
- eSata interface for high-speed back-up
- Built-in 3G(cdma2000/WCDMA) router (optional)
- Built-in GPS module
- Support external G-sensor module



Specifications

	DS-8008HMF(/GE)(/GW)	DS-8012HMF(/GE)(/GW)
Video/Audio input	Video compression	H.264
	Video input	8-ch
	Video input interface	Aviation interface (1.0Vp-p, 75Ω)
	Audio compression	OggVorbis, 16Kbps
	Audio input	8-ch
	Audio input interface	12-ch
Video/Audio output	Voice talk input	Aviation interface (linear electrical level, 1KΩ)
	Preview resolution	1 Aviation interface (linear electrical level, 1KΩ)
	VGA output	4CIF (PAL: 704x576, NTSC: 704x480)
	Recording resolution	1, resolution: 800×600/60Hz, 800×600/75Hz, 1024×768/60Hz
	Video output	4CIF/DCIF/2CIF/CIF/QCIF
	Frame rate	2-ch, aviation interface(1.0Vp-p, 75Ω)
Hard disk driver	Stream type	25(P)/30(N) fps
	Video bit rate	Video/Video&Audio
External interface	Audio output	32kbps~2048kbps, or user-defined
	HDD	2-ch (linear electrical level, 600Ω)
General	Technical patent	2 SATA interface, each max supports 2TB
	Communication interface	Hard disk vibration-proof technology
	3G antenna interface	1 RJ45 10M/100M adaptive Ethernet interface, 1 RS232 interface, 1 RS485 interface
	eSATA interface	2 antenna, SMA interface
	USB interface	1 E-SATA interface for high speed backup
	Alarm input	1 USB interface
	Alarm output	16-ch
	Remote control	4-ch
	GPS	IR remote controller built-in module, 1 antenna, SMA interface
Power input		
Power output		
Power off delay		
Scheduled on/off		
Consumption		
Working temperature		
Working humidity		
Dimension		
Weight(without HDD)		

Available Models

DS-8008HMF, DS-8008HMF/GE, DS-8008HMF/GW, DS-8012HMF, DS-8012HMF/GE, DS-8012HMF/GW

* /GE: built-in cdma2000 router;

* /GW: built-in WCDMA router;