

Ikegami

IK-9116/ 9016

16 ch Multiplexer

IK-9116 (16ch) B/W



IK-9016 (16ch) Color



Specifications

Model Number	IK-9116	IK-9016
Camera Type	B/W	Color
Video Input		
Camera Input	1 V p-p, 75 Ω x 16	
VCR Input	1 V p-p, 75 Ω x 1	
S-VHS VCR Terminal Input	N/A	Y: 1.0 V p-p, 75 Ω C: 0.286 V p-p, 75 Ω
Video Output		
Main Monitor	1 V p-p, 75 Ω x 1	
Call Monitor	1 V p-p, 75 Ω x 1	
Loop Through Out	1 V p-p, 75 Ω x 16	
VCR Output	1 V p-p, 75 Ω x 1	
S-VHS VCR Terminal Output	N/A	Y: 1.0 V p-p, 75 Ω C: 0.286 V p-p, 75 Ω
Relay Output	3	
Resolution	910 x 512 (NTSC) / 910 x 612 (PAL)	
Number of Grayscale/Color	256	16,700,000
Time/ Date	YES	
Camera Title	YES	
Covert Camera	YES	
2 X Zoom	YES	
Adjustable Alarm Hold Time	YES	
Adjustable Dwell Time	YES	
Built-in Buzzer	YES	
RS-232 port	YES	
Duplex Operation	YES	
Sensor Type	N. O. or N.C.	
Number of Alarm Input	16	
VCR Synchronization		
Programmable Field Delay	YES	
Switching Pulse Input	YES	
VCR Speed Auto Detection	YES	
VCR Record Time	2 (3 PAL) ~ 999 Hrs	
Priority Recording For Sensor-activated Channel	YES	
Key Lock	YES	
Power Consumption	12 V DC 20 W	
Dimensions	430 W x 200 D x 44.4 H (mm) / 17 W x 7.9 D x 1.75 H (inch)	
Weight	4.0 Kg/ 8.33 Lbs.	
Operating Temperature	0 to 50 °C (32 to 122 °F)	
Power Adapter	AC 100V~240 V in, DC 12 V out	
19" Rack Mountable	YES	
Motion Detection		
Rack Mounting Kit	Optional	
Remote Control	Optional	

Note: Specifications are subject to change without notice.