

16-Channel Triplex DVR with 2TB HDD incl.

LTV-DVR-1662-HV



- 16-channel triplex DVR
- 16 audio-channels
- H.264
- resolution and recording speed:
CIF/2CIF/ 4CIF/ 960H: 25 fps/ channel
- 3 monitor outputs (BNC+VGA+HDMI)
- 2TB HDD incl. (2 HDD SATA slots)
- 2 USB
- IR remote
- motion detector
- 16 alarm inputs/4 outputs
- telemetry
- Ethernet
- Power supply 12V included

Video/audio input	Video input	16xBNC (1.0Vp-p, 75Ω) PAL/NTSC
	Audio input	16xRCA (2.0Vp-p, 1kΩ)
	Two-way audio input	1xRCA (2.0Vp-p, 1kΩ)
Video/audio output	BNC output	1xBNC (1.0 Vp-p, 75 Ω)
	BNC resolution	PAL: 704x576; NTSC: 704x480
	HDMI/VGA output	1 HDMI & 1 VGA
	HDMI/VGA resolution	1920×1080P / 60 Hz, 1600×1200 / 60 Hz, 1280×1024 / 60 Hz, 1280×720 / 60 Hz, 1024×768 / 60 Hz
	Loop output	-
	Audio output	1xRCA (2.0Vp-p, 1KΩ)
Recording	Video compression	H.264
	Audio compression	G.711
	Stream type	Video / Video end audio
	Frame rate	WD1/4CIF/2CIF/CIF/QCIF; PAL:1/16—25fps, NTSC: 1/16—30fps
	Video bit rate	32...3072Kbps / or user defined, max 3072 Kbps
	Audio bit rate	64 Kbps
	Dual stream	Support; Sub-stream: CIF ,QCIF 25k/c
	Synchronous playback	16 ch
HDD	SATA	2xSATA
	Capacity	Up to 4TB capacity
Interface	Network	1xRJ45 10M / 100M
	Serial interface	1 RS-485
	USB	2xUSB 2.)
	Alarm input	16
	Alarm output	4
General	Input voltage	12V (DC)
	Consumption	≤20W
	Operating Temperature	-10°C...+55°C
	Operating Humidity	10...90%
	Box	Rack mount kit, 1U
	Dimension (W x D x H)	445×290×45 mm
	Weight (With hard disks)	≤4 kg