

HD-SDI Cameras

LTV-HCDM2-9200L-F3.6

HD-SDI Mini IR Dome Camera



Key Features:

- 2 MP CMOS Image Sensor
- Full HD1080p Video Output
- True Day/Night
- Privacy Masking, Eclipse
- OSD Menu
- Up to 20m IR Distance
- IP66 Casing



Camera	Imaging Device	1/3" Progressive Scan CMOS
	Signal System	PAL/NTSC
	Max. Resolution	1920(H)*1080(V)
	Min. Illumination	0.01 Lux @(F1.2,AGC ON), 0 Lux with IR
	Shutter Time	1/25 (1/30) s to 1/50,000 s
	Lens	3.6mm Angle of View: 80.9°
	Lens Mount	M12
	Adjustment Range	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°
	Day & Night	IR cut filter with auto switch
	Video Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
	HD Video Output	SMPTE292M (HD-SDI)
	Synchronization	Internal
	S/N Ratio	>52dB
Backlight Compensation	BLC	
Menu	Camera ID	On/off (15 characters, position programmable)
	Privacy Masking	8 programmable zones
	Gain Control	AGC
	Anti-flicker	On / Off
	Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
General	Operating Conditions	-10 °C ...+60 °C Humidity 90% or less (non-condensing)
	Power Supply	12 V DC±10%
	Power Consumption	Max. 5W
	Weather Proof	IP66
	IR-Lights	Built-in, up to 20 m
	Dimension	89.6 × 59.1 mm
	Weight	400 g