

SMART LINE

8 Channel PoE Recorder

LTV-NVR-SD0830P8



- **Main Features:**
- Max. 80 Mbps incoming bandwidth
- H.264/MJPEG dual codec decoding
- All channel synchronous realtime playback, GRID interface
- ONVIF Version 2.3 compliant



Video	
IP Camera Input	8 channel
Two-way Talk	1 channel Input, 1 channel Output, RCA
Display	
Interface	1 HDM1, 1 VGA
Resolution	1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768
Display Split	1/4/8/9
Recording	
Compression	H.264/MJPEG
Resolution	5MP(2560 x 1920), 3MP(2048 x 1536) 1080P (1920 x 1080), 720P(1280 x 720) D1(704 x 576/704 x 480)
Record Rate	80 Mbps
Bite Rate	48 ~ 8192kbps
Record Mode	Manual, Schedule (Regular(Continuous), MD, Alarm), Stop
Record Interval	1 ~ 120min (default: 60min), Pre-Record: 1 ~ 30sec, Post-record: 10 ~ 300sec
Video Detection	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22 x 18), Video Loss & Camera Blank
Playback & Backup	
Sync Playback	1/4/9
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Network	
Ethernet	1 RJ-45 port (10/100Mbps)
PoE	8 ports (IEEE802.2at)
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDMS, FTP, Alarm Server, IP Search
Smart Phone	iPhone, iPad, Android
Miscellaneous	
Internal HDD	1 SATA, 1TB HDD included
Power Supply	Single, DC 48V / 1.5A
Power Consumption	NVR: 10W (without HDD)
	PoE: Max. 25.5W for single port
Working Environment	-10°C ... +55°C / 10% ~ 90%RH / 89 ~ 106kpa
Dimensions	37 x 270 x 205 mm (HxWxD)
Weight	0,7 kg (without HDD)