

## ECONOMY LINE

### 16 Channel Plug&Display PoE NVR with 2TB HDD

LTV RNE-161 0G

Article-No.: 23100017



#### Main Features:

- 3 Mpix resolution
- 4 channel playback
- H.264 High Profile
- Dual Streaming
- Apps



System	
Compression	Standard H.264
OS	Embedded Linux
Pentaplex	Preview, record, playback, backup, remote access
Video	
Output	HDMI × 1 (1920 x 1080) / VGA × 1 (1920 x 1080)
IP Input	
3Mpix/ 1080P/ 720P	16 CH 3MP / 1080P / 960P / 720P @30 fps
Audio	
Input	16 CH IPC input
Output	RCA x 1
2-way Audio	RCA x 1
Recording	
Resolution	3MP : 2048 x 1536, 1080P : 1920 x 1080, 960P : 1280 x 960 720P : 1280 x 720, D1 : 704 x 576
Framerate	200 fps ( PAL ) / 240 fps ( NTSC )
Bitrate	256 Kbps ~ 12 Mbps
Encode	CBR
Quality	6 levels
Mode	Manual, timer, motion, sensor
File Manager	Lock, unlock, reserving time
Playback	
Playback	4 channel
Search	Time / calender search, event (motion, external alarm)
Functions	Play, pause, FF, FB, digital zoom
Alarm	
Mode	Sensor, motion, video loss
Input	No local input, support IPC alarm input
Output	No
Triggering	Record, e-mail, etc.
Network	
Interface	RJ45 x 1 10M/100M/1000M
Protocols	TCP / IP,UDP, DHCP,DNS, PPPOE, DDNS, Email
Others	20 users online, dual stream
Smartphone	
OS	iPhone, Android
Functions	Multi-screen surveillance (for certain model), record, snapshot, save the device list
Data Storage	
Backup	Network, USB backup device
HDD	SATA x 1
Ports	
RS485	No
PoE	RJ45 x 8, with POE
PoE Power Potential	8W / Port
PoE max. Consumption	12.95W (802.3AF) / Port
USB	USB 3.0: 1 x for USB backup device USB 2.0: 1 x for mouse or USB backup device
Miscellaneous	
Dimensions	300mm × 270mm × 58mm (WxDxH)
Delivery Content	SATA cable, USB mouse
Power Supply	<12W (without HDD) / 12V (DC) + 48V (DC)
Operating Temperature	-10°C ...+55°C (temperature), 10% ... 90% (humidity)