

# HiRes IP Cameras And Accessories

## Camera Models M24

**Model:**

**Indoor/Outdoor:**

**Lenses:** (eq. 35mm)

**Resolution:**

**Pan/Tilt/Zoom:**

**Frame Rate (max.):**

**Sensitivity:**

**Interfaces:**

**Internal DVR:**

**Audio/Telephony:**

**Power Sup. • In/Out:**

**Software Features:**

**Arming • Triggering:**

**External Storage:**

**Prices:**

**M24M-IT-D22**

In/Outdoor, IP66, -30 to +60 °C  
 Super Wide Angle (22mm, 90°, F 2.0),  
 VGA (640x480 pixels), color  
 Continuous 8x zoom & pan/tilt (digital)  
 30 fps CIF • 30 fps VGA  
 1 lux (f=1/60s) • 0.05 lux (f=1/1s)  
 Ethernet 10/100, USB, MxBus  
 Up to 64 GB with MicroSD card  
 Bidirectional, IP telephony (VoIP)  
 PoE (IEEE 802.3af) • Via ExtIO  
 FTP, e-mail, video alarm management,  
 VideoMotion, Multiview, event search  
 365 day schedule • Multiple events  
 Up to 1 TB on PC/Server/NAS

**£578 (MX-M24M-IT-D22)**

**M24M-Sec**

In/Outdoor, IP66, -30 to +60 °C  
 Super Wide Angle (22mm, 90°, F 2.0), 32mm,  
 43mm, 65mm, 135mm  
 3MEGA (2048x1536 pixels), color  
 Continuous 8x zoom & pan/tilt (digital)  
 30 fps VGA • 30 fps MEGA • 20 fps 3MEGA  
 1 lux (f=1/60s) • 0.05 lux (f=1/1s)  
 Ethernet 10/100, USB, MxBus  
 Up to 64 GB with MicroSD card  
 Bidirectional, IP telephony (VoIP)  
 PoE (IEEE 802.3af) • Via ExtIO  
 FTP, e-mail, video alarm management,  
 VideoMotion, Multiview, event search  
 365 day schedule • Multiple events  
 Up to 1 TB on PC/Server/NAS

**£738 (MX-M24M-Sec)**

**M24M-Sec-Night**

In/Outdoor, IP66, -30 to +60 °C  
 Super Wide Angle (22mm, 90°, F 2.0), 32mm,  
 43mm, 65mm, 135mm  
 MEGA (1280x960 pixels), B/W  
 Continuous 8x zoom & pan/tilt (digital)  
 30 fps VGA • 30 fps MEGA  
 0,1 lux (f=1/60s) • 0.005 lux (f=1/1s)  
 Ethernet 10/100, USB, MxBus  
 Up to 64 GB with MicroSD card  
 Bidirectional, IP telephony (VoIP)  
 PoE (IEEE 802.3af) • Via ExtIO  
 FTP, e-mail, video alarm management,  
 VideoMotion, Multiview, event search  
 365 day schedule • Multiple events  
 Up to 1 TB on PC/Server/NAS

**£738 (MX-M24M-Sec-Night)**

**Model:**

**Indoor/Outdoor:**

**Lenses:** (eq. 35mm)

**Resolution:**

**Pan/Tilt/Zoom:**

**Frame Rate (max.):**

**Sensitivity:**

**Interfaces:**

**Internal DVR:**

**Audio/Telephony:**

**Power Sup. • In/Out:**

**Software Features:**

**Arming • Triggering:**

**External Storage:**

**Prices:**

**M24M-Sec-CSVario**

In/Outdoor, IP66, -30 to +60 °C  
 CSVario 24-54 (24 bis 54mm)  
 F1.6-2.3  
 3MEGA (2048x1536 pixels), color  
 Continuous 8x zoom & pan/tilt (digital)  
 30 fps VGA • 30 fps MEGA • 20 fps 3MEGA  
 1 lux (f=1/60s) • 0.05 lux (f=1/1s)  
 Ethernet 10/100, USB, MxBus  
 Up to 64 GB with MicroSD card  
 Bidirectional, IP telephony (VoIP)  
 PoE (IEEE 802.3af) • Via ExtIO  
 FTP, e-mail, video alarm management,  
 VideoMotion, Multiview, event search  
 365 day schedule • Multiple events  
 Up to 1 TB on PC/Server/NAS

**£938 (MX-M24M-Sec-CSVario)**

**M24M-Sec-D11**

In/Outdoor, IP66, -30 to +60 °C  
 Hemispheric (11mm, 360°, F 2.0)  
 3MEGA (2048x1536 pixels), color  
 Continuous 8x zoom & pan/tilt (digital)  
 30 fps VGA • 30 fps MEGA • 20 fps 3MEGA  
 1 lux (f=1/60s) • 0.05 lux (f=1/1s)  
 Ethernet 10/100, USB, MxBus  
 Up to 64 GB with MicroSD card  
 Bidirectional, IP telephony (VoIP)  
 PoE (IEEE 802.3af) • Via ExtIO  
 FTP, e-mail, video alarm management,  
 VideoMotion, Multiview, event search  
 365 day schedule • Multiple events  
 Up to 1 TB on PC/Server/NAS

**£798 (MX-M24M-Sec-D11)**

**M24M-Sec-Night-N11**

In/Outdoor, IP66, -30 to +60 °C  
 Hemispheric (11mm, 360°, F 2.0)  
 MEGA (1280x960 pixels), SW  
 Continuous 8x zoom & pan/tilt (digital)  
 30 fps CIF • 30 fps VGA • 30 fps MEGA  
 0,1 lux (f=1/60sec) • 0.005 lux (f=1/1sec)  
 Ethernet 10/100, USB, MxBus  
 Up to 64 GB with MicroSD card  
 Bidirectional, IP telephony (VoIP)  
 PoE (IEEE 802.3af) • Via ExtIO  
 FTP, e-mail, video alarm management,  
 VideoMotion, Multiview, event search  
 365 day schedule • Multiple events  
 Up to 1 TB on PC/Server/NAS

**£798 (MX-M24M-Sec-Night-N11)**

## Accessories M22/M24

**Part Name:**

**Description:**

**Prices:**



**Ethernet patch cable for M24 (1/2/5/10 m)**

- 2x RJ45 plug with special MOBOTIX seal
- 1, 2, 5 or 10 m long

**from £8 (MX-OPT-CBL-LAN-1)**



**M12/M22/M24-Pole Mount**

- 3mm stainless steel, white
- Pole mounting
- Pole circumference from 60 to 180mm
- 2 x stainless steel straps, screws and washers included

**£78 (MX-MH-SecureFlex-ESWS)**



**ExtIO**

- Each with 2 In- and Output contacts 8-24V
- Microphone with adjustable volume control, speaker, status LEDs
- USB interface, illumination sensor
- Temperature sensor, 2 buttons

**£188 (MX-ExtIO)**