

BL-C140 Network Static Camera

The splash-resistant body lets you install the camera outside

Power supply via LAN cable (proprietary PoE)

MPEG-4 and JPEG images can be simultaneously sent

HTTPS data encrypted communication prevents electronic eavesdropping

Full screen display can be monitored the objects bigger

Colour night view mode allows you to see clear images even in the dark



Splash-resistant network camera with MPEG-4/JPEG monitoring and proprietary PoE capability

General Data

| | |
|--------------------------|------|
| Power Supply | 9V |
| Power Consumption | 3,2W |

Dimensions (mm)

| | |
|------------------------------|-----------------------------|
| Width | 106.0 |
| Height | 106.0 |
| Depth | 57.0 |
| Operating Temperature | -20°C to +50°C |
| Operating Humidity | 20% – 90% (no condensation) |

Features

| | |
|--------------------------|--|
| Video Resolution | 640 × 480 320 × 240 192 × 144 |
| Illumination | Directly in front of camera: About 8.5 lx; 20° to left/right of camera: About 2.5 lx |
| Video Compression | JPEG (3 levels), MPEG-4 |
| Motion Detection | yes |

System Requirements for PC Control

| | |
|----------------------------|--|
| Supported Protocols | IPv4/IPv6 Dual-Stack. IPv4: TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS, ARP, ICMP, POP3, NTP, UPnP™, SMTP Authentication, RTP, |
|----------------------------|--|

RTSP, RTCP, HTTPS, SSL, TLS. IPv6: TCP, UDP, IP, HTTP, FTP, SMTP, DNS, ICMPv6, POP3, NDP, NTP, RTP, RTSP, RTCP, HTTPS, SSL, TLS.

| | |
|---------------------------------------|--|
| Image Transfer Method | SMTP, FTP, HTTP |
| Image Buffer/Transfer Triggers | Timer, Motion Detection |
| Memory Capacity | About 250 frames (320 × 240, standard image quality) |
| Indicator Display | Power, Camera Operation, Ethernet Link |

Camera

| | |
|-------------------------|------------------------------|
| Type | 1/4 inch CMOS sensor |
| Effective Pixels | 320.000 pixels |
| Frame Rate | Max. 30 frames/second |
| Viewing angle | Horizontal 58°, Vertical 45° |
| Lens | Fixed Focus, 0,3m–Infinity |
| Zoom Ratio | 10× (by area) digital zoom |

Network

| | |
|----------------|--|
| Network | 10Base-T/100Base-TX Ethernet RJ-45 connector |
|----------------|--|
