



## RVX28 RVX28-W (wiper)

All X-SERIES cameras can be configured as either conventional Domes or Ball type Pan & Tilts. Cameras are supplied as Domes, but can easily be transformed to Pan & Tilts by removing the Dome Top Cover.

### Dome Configuration.

X-series domes all have flat toughened glass windows providing superior optics compared to conventional Dome bubbles. Unlike conventional Domes the X-series Cameras can see above the horizon without the video picture being clipped by the Dome top.

### Ball PTZ Configuration.

X-Series Ball PTZ can be inverted and tower mounted. This mounting option provides full 360 vision.



PEDESTAL

SWAN

WALL

PENDANT

Redvision CCTV Ltd, 17 Highview, High Street, Bordon, Hampshire, GU35 0AX, UK



# X-SERIES

**RVX28 RVX28-W** (wiper)

## Key Features

- Cameras supplied as Dome-Easy convert to PTZ
- Rugged Aluminium casting and toughened window
- 0.1/second to 200/second for precise control
- 28X Sony FCB Camera Module
- Up the Coax and 485 control options
- 100 presets, 8 tours, alarm options
- Privacy, 24 programmable zones
- Wiper option available
- Versions available with IR

## Specification

Camera Module FCB-EX980EP. 28 X module 530 TV lines. Colour/mono TDN.

### Mechanical:

Material Powder coat die cast aluminium. Toughened glass window  
Environment -35°C to +50°C. IP 66.  
Weight 7Kg.

### Telemetry:

RS 485 Pelco P, Pelco D,  
Coaxial BBV.


### Power Supply Options:

RV-PSU 110-240V input. 24VDC 2A output.  
RV-PSU-ALM16 PSU including 16 alarm inputs.  
RV-PSU-ALM16-W PSU with 16 alarm inputs and wireless PIR interface.

## Order Codes

RVX28 X-Series Dome/PTZ Camera.  
RVX28-W X-Series Dome/PTZ Camera with Wiper.

## Mounting Bracket Options:



RV-POLE



RV-CNR



RV-SWAN



RV-WALL



RV-PED

Redvision CCTV Ltd, 17 Highview, High Street, Bordon, Hampshire, GU35 0AX, UK