

Data Sheet

Constellation® ES.2

2TB and 3TB Capacity-Optimised Enterprise
Hard Drives for Bulk-Data Applications

Key Advantages

- Highest-capacity enterprise drive for demanding data growth¹
- Fifth-generation SAS and SATA drives designed for 24x7 reliability
- SAS-based, end-to-end data integrity and enhanced error correction for accurate data storage
- Best-in-class enhanced rotational vibration tolerance ensures consistent performance
- Improved power and cooling efficiencies with low power consumption and enhanced PowerChoice™ technology
- Multi-drive firmware maximised for enterprise system availability
- Robust performance with dual processor and ramp load technologies
- Self-Encrypting Drive (SED) option (AES-256) cuts IT drive retirement costs while protecting data securely where it lives — on the drive²
- FIPS 140-2 Validated™ drives protect data classed as *Sensitive but Unclassified* and *Protected*^{2,3}

Best-fit Applications

- High-capacity bulk data storage
- Mainstream enterprise external storage arrays (SAN, NAS, DAS)
- Enterprise backup and restore — D2D, virtual tape
- Centralised surveillance
- Cloud storage

¹ Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full 3TB capacity capabilities.

² Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries; may require TCG-compliant host or controller support.

³ See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>



Constellation® ES.2



2TB and 3TB Capacity-Optimised Enterprise Hard Drives for Bulk-Data Applications

Specifications	6Gb/s SAS		SATA 6Gb/s	
	3TB ^{1,2}	2TB ¹	3TB ^{1,2}	2TB ¹
Standard Model Number	ST33000650SS	ST32000645SS	ST33000650NS	ST32000645NS
SED (AES-256) Model Number	ST33000651SS ³	ST32000646SS ³	ST33000651NS ³	ST32000646NS ³
SED (AES-256) Model Number	ST33000652SS ^{3,4}	ST32000647SS ^{3,4}	ST33000652NS ^{3,4}	ST32000647NS ^{3,4}
Features				
Protection Information	Yes	Yes	—	—
Low Halogen	Yes	Yes	Yes	Yes
Cache, Multi-segmented (MB)	64	64	64	64
Reliability/Data Integrity				
Mean Time Between Failures (MTBF, hours)	1.2 million	1.2 million	1.2 million	1.2 million
Reliability Rating at Full 24x7 Operation (AFR)	0.73%	0.73%	0.73%	0.73%
Non-recoverable Read Errors per Bits Read	1 sector per 10 ¹⁵	1 sector per 10 ¹⁵	1 sector per 10 ¹⁵	1 sector per 10 ¹⁵
Power-On Hours per Year	8,760	8,760	8,760	8,760
Bytes per Sector	512, 520, 528	512, 520, 528	512	512
Limited Warranty (years) ⁵	5	5	5	5
Performance				
Spindle Speed (RPM)	7,200	7,200	7,200	7,200
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5
Max Sustained Transfer Rate (MB/s)	155	155	155	155
Seek Time, Average Read/Write (ms)	8.5/9.5	8.5/9.5	8.5/9.5	8.5/9.5
Average Latency (ms)	4.16	4.16	4.16	4.16
Interface Ports	Dual	Dual	Single	Single
Rotational Vibration @ 1,500Hz (rad/sec ²)	12.5	12.5	12.5	12.5
Power Consumption				
Idling (W)	7.4	7.4	7.7	7.7
Typical Operating, Random Read (W)	11.3	11.3	10.7	10.7
Power Supply Requirements	+12V and +5V	+12V and +5V	+12V and +5V	+12V and +5V
PowerChoice™ Technology	Yes	Yes	Yes	Yes
Environmental				
Temperature, Operating (°C)	5 to 60	5 to 60	5 to 60	5 to 60
Vibration, Non-operating: <5Hz to 500Hz(Gs)	4.9	4.9	4.9	4.9
Shock, Operating, 2ms (Read/Write) (Gs)	70/40	70/40	70/40	70/40
Shock, Non-operating, 1ms and 2ms (Gs)	300	300	300	300
Physical				
Height (in/mm, max) ⁶	1.028/26.11	1.028/26.11	1.028/26.11	1.028/26.11
Width (in/mm, max) ⁶	4.010/101.85	4.010/101.85	4.010/101.85	4.010/101.85
Depth (in/mm, max) ⁶	5.787/147.00	5.787/147.00	5.787/147.00	5.787/147.00
Weight (lb/g)	1.543/700	1.543/700	1.543/700	1.543/700
Carton Unit Quantity	20	20	20	20
Cartons per Pallet	40	40	40	40
Cartons per Layer	8	8	8	8

¹ One gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.

² Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full 3TB capacity capabilities.

³ Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries; may require TCG-compliant host or controller support.

⁴ See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>

⁵ Nearline products shipped between 31 December 2011 and 30 June 2012 have a 3-year limited warranty. Nearline products shipped before 31 December 2011 or after 30 June 2012 have a 5-year limited warranty.

⁶ These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8223.



www.seagate.com

AMERICAS
ASIA/PACIFIC
EUROPE, MIDDLE EAST AND AFRICA

Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, +1 408 658 1000
Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888
Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, +33 1 41 86 10 00