


550 TV Line Security Camera with 36x Optical Zoom Lens and High-speed 360° Endless Panning Function

- Horizontal resolution of 550 TV lines
- 360° endless rotation and 15° above-the-horizon tilt
- 36x optical zoom lens
- DynaView™
- Optical Day/Night function



KEY FEATURES


- High-speed 360 degree endless rotation (up to 300 °/s)
- Above-the-horizontal tilt - 15° tilt-up, total tilt range of 210°



- 36x optical and total zoom ratio of 432x with 12x digital zoom
- High sensitivity (1.4 lx, F1.6, 50 IRE) achieved by 1/4-type CCD with ExwaveHAD™ technology

ExwaveHAD™

- DynaView — Wide-D technology to handle various lighting conditions in a scene




- Optical Day/Night function to switch to Day or Night mode depending on the light level
- Eight-zone privacy masking on any position of the video image
- Alarm I/O function — The camera and external devices can be controlled by alarm inputs and outputs
- Motion Detection function — Users can set up the camera to trigger a video recorder or to send an alarm signal to an external device when it detects motion
- Stabilizer function that is effective to stabilize the gentle vibration of an image*
- 128 preset positions and 5 preset tours

* This function employs a digital zoom system and the image may be cropped slightly.

SPECIFICATIONS

SSC-CR481	
Camera	
Image device	1/4-type EXview HAD CCD
Signal system	PAL standard
Horizontal resolution	550 TV lines
S/N ratio	More than 50 dB (Weight: ON)
Minimum illumination	Color: 1.40 lx, B/W: 0.15 lx (F1.6, 50 IRE, AGC ON)
	Color: 0.90 lx, B/W: 0.10 lx (F1.6, 30 IRE, AGC ON)
Video output	VBS: 1.0 Vp-p
Synchronization	Internal/AC line lock selectable
Gain control	Auto/Manual (-3 dB to +28 dB)
White balance	ATW/AUTO/ONE PUSH/INDOOR/OUTDOOR/SODIUM LAMP/MANUAL
Lens type	Auto-focus zoom lens
Zoom ratio	36x
Horizontal viewing angle	1.7 degrees to 57.8 degrees
Focal Length	f=3.4 mm to 122.4 mm
F number	F1.6 (wide) to F4.5 (tele)
Minimum object distance	320 mm (wide) to 1,500 mm (tele)
Pan/Tilt angle	360 degrees endless rotation/210 degrees
Pan/Tilt speed	0.1 degrees/s to 300 degrees/s
Preset position	128
Tour	5
Camera Features	
Day/Night	Yes
Wide-D	Yes (DynaView)
Noise reduction	Yes
Stabilizer	Yes
General	
Mass	1.7 Kg (3 lb 12 oz) (including ceiling bracket)
Dimensions	ø147.4 mm x 190.9 mm (5 7/8 inches x 7 5/8 inches)
Power requirement	AC 24 V ±10%
Power consumption	19 W
Operating temperature	-10 °C to +50 °C (14 °F to 122 °F)
Storage temperature	-20 °C to +60 °C (-4 °F to 140 °F)
Supplied accessories	Ceiling bracket (1), Operating Instructions (1), Screw (2), Template (1), 24 V AC connector (1), I/O connector (1)

DIMENSIONS



Distributed by

© 2012 Sony Corporation. All rights reserved.
 Reproduction in whole or in part without written permission is prohibited.
 Features and specifications are subject to change without notice.
 The values for weight and dimension are approximate.
 "Sony", "make.believe", "Exwave HAD", and "DynaView" are
 trademarks of Sony Corporation.
 All other trademarks are the property of their respective owners.