

# DigiEye

## The Multifunctional Digital Security Management System



### MOTHERBOARD

**CPU** - Pentium 4 @ 2.4 GHz

**RAM** - 512 MB

**Expansion slots** - 2 PCI slot for optional RAID interface and RS232/485 expansion

**Watchdogs** - 2: one on the motherboard, one on the Frame Grabber board

### VIDEO

**Video Inputs** - 16 composite video inputs for Color PAL or NTSC cameras, B/W CCIR or EIA cameras; 16 BNC connectors for camera inputs (1 Vpp/75 Ohm); 16 BNC connectors signal looped for each camera (1 Vpp/75 Ohm)

**Video Outputs** - 4 composite video outputs (CVBS) on BNC connectors (1 Vpp/75 Ohm), from internal video matrix switcher

**Console output** - SVGA monitor output; DB15-S VGA connector

**Image resolution** - PAL: 640x512, 640x256 or 320x256 pixels; NTSC: 640x480, 640x240 or 320x240 pixels

**Image compression** - Enhanced Delta®

**Acquisition rate** - 200/240 fields per second (PAL/NTSC)

**Recording rate** - Multiplexed up to 200/240 fields per second (PAL/NTSC)

**Compression ratio** - Typical for complete image 1:80 to 1:8 (from 8 to 80 kbyte) plus further reduction (from 0 % to 99%) proportional to variation between subsequent images

**Motion detection** - Executed in real time on each acquired image on complete image, or on multiple areas (of any number, shape, position and size)

### AUDIO

**Audio compression** - G723.1 (8KHz sampling, final coding at 6.4 or 5.3 Kbit/s)

**Required storage** - Approximately 3 MB /hour

### STORAGE

**Hard drives** - Two 3½" IDE drives and RAID support

**Backup** - One internal CD/DVD- RW and support for USB removable devices as PenDisk etc.

### INTERFACES

**Serial ports** - 2 serial ports RS-232, 2 PS/2 ports for mouse and keyboard, 5 USB (4 rear, 1 frontal)

**Local Area Network** - 100BaseT, RJ-45 connector

**Audio interface** - Line out, line in, mic in on 3.5mm stereo jack

**Digital inputs** - 18 dry contact opto coupled

**Digital outputs** - 18 relay dry contact

### COMMUNICATIONS

**Supported media** - IP networks, PSTN/POTS, ISDN, ADSL, HDSL, LAN, GPRS

### GENERAL

**Power supply** - 110/230 VAC, 350W

**Dimensions (WxDxH)** - 19" 4U rack. (435 x 535 x 177 mm) / (17,1 x 21,1 x 7 inch). Max including BNC, handle and accessories (485 x 580 x 185 mm) / (19,1 x 22,8 x 7,3 inch)

**Weight** - 18 Kg / 39,7 lbs

**Operating temperature** - +5-+50 C°

**Max relative humidity** - 5-95% non-condensing

For further information, please contact us at [info@syac.com](mailto:info@syac.com) or visit our website - [www.syac.com](http://www.syac.com)