

# Verint RP 500 Series Dome Cameras

## *For Mobile Transportation Applications*

Verint® RP 500 Series dome cameras are robust and reliable digital video solutions for buses, trains, light rail, and other mobile transportation applications.

The RP 500 Series is built to deliver clear, crisp images under virtually any lighting conditions. A compact and rugged polycarbonate housing makes these cameras resistant to vandalism, with rounded edges to protect against passenger injury.

Designed for round-the-clock operation, Verint mobile cameras capture up to 470 TV Lines (TVL) color and 570 TVL black-and-white, automatically switching from color to black-and-white in low light conditions.

The RP 500 Series is part of Verint's comprehensive suite of mobile video solutions for transportation systems.

### **Verint. Powering Actionable Intelligence.®**

Verint Systems (NASDAQ: VRNT) is a leading global provider of analytic software-based solutions for communications interception, networked video, and business intelligence. Verint solutions transform voice, video, and text into *actionable intelligence* – timely, mission-critical insights for achieving strategic goals.

Since 1994, Verint has been committed to developing innovative solutions that help our customers achieve their most important objectives. Today, more than 1000 organizations in over 50 countries use Verint's actionable intelligence solutions to enhance security, boost operational efficiency, and fuel profitability.

### KEY FEATURES

- ✓ Rugged, vandalism-resistant polycarbonate dome housings
- ✓ Suitable for train and bus installations – Can be wall or ceiling mounted
- ✓ High resolution: up to 470 TVL color, 570 TVL black and white
- ✓ Supports day and night operation
- ✓ Specially constructed to withstand vibration of mobile environments
- ✓ Easy installation



### SAFE ON THE MOVE™

Verint helps transportation providers protect people and property, refute false claims, and reduce frivolous lawsuits.

Verint RP 500



*Designed for highly reliable operation in demanding transportation environments, Verint Mobile Video Solutions readily address the challenges of continuous vibration, extreme temperatures, and frequent power fluctuations.*

	Verint RP 505K	Verint RP 506K	Verint RP 506L
CCD Sensor	1/3" Sony Super HAD Interline CCD	1/3" Sony Exview Interline CCD	1/3" Sony Super HAD Interline CCD
Max. Pixels (H X W)	CCIR: 752 x 582 EIA: 768 x 494	PAL: 752 x 582 NTSC: 768 x 494	PAL: 752 x 582 NTSC: 768 x 494
Horizontal Resolution	570 TV Lines	470 TV Lines	470 TV Lines
Min. Illumination]	0.0075 lux at the sensor / 0.15 lux @ F2.0	0.015 lux at the sensor / 0.3 lux @ F2.0	0.02 lux at the sensor / 0.4 lux @ F2.0
Scanning System	CCIR: 625 lines; 50 Hz EIA: 525 lines; 60 Hz	PAL: 625 lines; 50 Hz NTSC: 525 lines; 60 Hz	PAL: 625 lines; 50 Hz NTSC: 525 lines; 60 Hz
Enhancer	Yes	Yes	Yes
Gamma Correction	0.45	0.45	0.45
Electronic Shutter	Automatic CCIR: 1/50-1/100,000 sec. EIA: 1/60-1/100,000 sec.	Automatic PAL: 1/50-1/100,000 sec. NTSC: 1/60-1/100,000 sec.	Automatic PAL: 1/50-1/100,000 sec. NTSC: 1/60-1/100,000 sec.
Signal to Noise Ratio	46 dB (AGC off)	46 dB (AGC off)	46 dB (AGC off)
AGC	30 dB	30 dB	26 dB
Synchronization	Internal	Internal	Internal
Backlight	Automatic	Automatic	Automatic
Spectral Response	380 - 1000 nm	380 - 660 nm	380 - 660 nm
Smear Effect	0.01%	0.005%	0.01%
Video Output Signa	Monochrome BAS 1Vpp / 75 Ohm, BNC	FBAS 1Vpp / 75 Ohm, BNC	FBAS 1Vpp / 75 Ohm, BNC
Operation Voltage	12V/DC (DC 8.0-15.0 V)	12V/DC (DC 8.0-15.0 V)	12V/DC (DC 8.0-15.0 V)
Consumption	Maximum 2W	Maximum 2W	Maximum 2W
Ambient Temperature	14°F to +122°F	14°F to +122°F	14°F to +122°F
Air Humidity	Up to 90%	Up to 90%	Up to 90%
IP Rating	IP41, class III	IP41, class III	IP41, class III
MTBF	80,000 hours	80,000 hours	80,000 hours
Housing	Dome camera with clear dome bubble	Dome camera with clear dome bubble	Dome camera with clear dome bubble
Connectors	Terminal block, wiring cable	Terminal block, wiring cable	Terminal block, wiring cable
Weight	0.77 lbs or 1.21 lbs including mounting ring	0.77 lbs or 1.21 lbs including mounting ring	0.77 lbs or 1.21 lbs including mounting ring
Mounting	Ceiling or wall mount	Ceiling or wall mount	Ceiling or wall mount
Lens	2.1mm; 2.9mm; 3.6mm; 4.3mm; 6mm; 8mm	2.1mm; 2.9mm; 3.6mm; 4.3mm; 6mm; 8mm	2.1mm; 2.9mm; 3.6mm; 4.3mm; 6mm; 8mm
Dimensions (D/H)	4.29" / 2.95"	4.29" / 2.95"	4.29" / 2.95"

By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice.

Verint, Actionable Intelligence, BehaviorTrack, Dellis, HealthCheck, I-Rooms, Lanex, Loronix, Loronix Video Manager, MotionTrack, microDVR, nDVR, NetDVR, Nextiva, Powering Actionable Intelligence, RP Security, Safe on the Move, SmartSight, Video Manager, and WebReview are trademarks of Verint Systems Inc., its subsidiaries or affiliates. All other registered trademarks, trademarks, and any associated logos are the properties of their respective owners.

© 2005 Verint Systems Inc. All rights reserved.

Email: [mobilesales@verint.com](mailto:mobilesales@verint.com)

Phone: 1-800-638-5969

Or on the web at: [www.verint.com/videosolutions](http://www.verint.com/videosolutions)

330 South Service Road, Melville, NY 11747 USA

November 2005

