

Nextiva S1708e

Multi-Port, DVD-Quality Ethernet Video Server

The Nextiva™ S1708e is a multi-port, DVD-quality Ethernet video server with on-board analytics, designed for video monitoring and surveillance over IP networks.

Fully integrated with the Nextiva platform and applications, these analytics "at the edge" can dramatically reduce video transport and storage requirements and leverage all Nextiva capabilities, including automated health monitoring, event notification, and rules-based video distribution.

Built on accepted industry standards, Nextiva S1708e Intelligent Edge Devices provide high availability and easy interoperability with your IT and enterprise systems.

Easy to Configure and Manage

Nextiva Control Center, an easy-to-use management portal, simplifies deployment and enables you to configure and administer your S1708e from a single location and application. The Nextiva S1708e can also be configured and managed using Verint® nDVR™ or Verint Loronix Video Manager™.

Nextiva S1708e Intelligent Edge Devices add value to your existing video investments and provide a path for growth.

Verint. Powering Actionable Intelligence.®

Verint Systems (NASDAQ: VRNT) is a leading global provider of analytic software-based solutions for communications interception, networked video, and business intelligence. Verint solutions transform voice, video, and text into *actionable intelligence* – timely, mission-critical insights for achieving strategic goals.

Since 1994, Verint has been committed to developing innovative solutions that help our customers achieve their most important objectives. Today, more than 1000 organizations in over 50 countries use Verint's actionable intelligence solutions to enhance security, boost operational efficiency, and fuel profitability.

KEY FEATURES

- ✓ DVD-quality, 8-port encoder
- ✓ Dual-stream, MPEG-4 SP video up to 4CIF, 30 FPS
- ✓ Powerful on-board analytics
- ✓ RS-422/485 serial port to support motorized domes and cameras
- ✓ RS-232 serial port for integration with access control systems
- ✓ Optional bi-directional audio interface
- ✓ Compact design accommodates 8 video streams in a 1U, 6-inch (15-cm) deep enclosure
- ✓ Automated configuration, health monitoring, and diagnostics with Nextiva



Nextiva Intelligent Edge Devices address security and performance challenges across a wide range of environments and applications.

The Nextiva S1708e Ethernet Video Server offers DVD-quality images, high frame rates, and a lower cost per port.

Nextiva S1708e



VERINT
POWERING ACTIONABLE INTELLIGENCE®

Technical Specifications

NETWORK

Interface	Ethernet 10/100Base-T
Connector	RJ-45 jack
Protocols	Transport: RTP/IP, UDP/IP, TCP/IP, or multicast IP Others: DNS, NTP, HTTP, FTP, and DHCP client
Security	SSL-based authentication

VIDEO

Input	8 composites, 1 Vpp into 75 ohms (NTSC/PAL)
Dual Stream Connectors	4CIF, 30 FPS and CIF, 15 FPS programmable BNC female connectors
Compression	MPEG-4 SP
Resolution	Scalable from 352 x 240 to 704 x 480 NTSC pixels (352 x 288 to 704 x 576 PAL pixels)
Frame Rate	8 x 1-30 FPS in NTSC (1-25 FPS in PAL) programmable (full motion)
Bandwidth	Each stream configurable 30 kbps to 6 mbps

SERIAL PORT

Electrical Levels	Port 1: RS-232 (max. 230 kbps) Port 2: RS-422/485 2/4 wires (max. 230 kbps)
Connectors	Port 1: DB-9 female (DCE) Port 2: pluggable screw-terminal strip
Operating Mode	Transparent serial port supporting any asynchronous serial protocol

ALARM AND AUDIO

Alarm	Input: 12 dry contacts Output: 2 relay contacts (48V AC/DC at 100 mA max.)
Bi-directional Audio (optional)	1 input (optional 12 input ports): -46 to -3 dBV into 30 kOhm (line or microphone input) Output: -46 to -3 dBV into 8 ohms min.
Uni-directional Audio (optional)	12 inputs: -46 to -3 dBV into 30 kOhm (line or microphone input) Programmable bias: 0-9V DC 16-bit resolution 8, 16, or 24 KHz sampling rate Connectors: One set of 1/8 in. (3.5 mm) input and output stereo jacks

POWER

Supply Voltage	12V DC +/- 10% (20W)
----------------	----------------------

PHYSICAL

Enclosure	Metal case with flange mount (black color)
Dimensions	17L x 6.1W x 1.7H in. (431.8L x 154.9W x 43.2H mm)
Weight	5.3 lb (2.4 kg)
Environmental	32°F to 122°F (0°C to 50°C)
Humidity	95% non-condensing at 122°F (50°C)

MANAGEMENT

Configuration *	Remote: via Nextiva, nDVR, Loronix Video Manager, SConfigurator, or Telnet Local: via the serial port using any ASCII terminal
Firmware Upgrade	Flash memory for upgrade of video codec and application firmware over the network; remote batch upgrade available through Nextiva Control Center

CERTIFICATION AND REGULATION

USA	UL, FCC part 15 (subpart B, class A)
Canada	ICES-003/NMB-003
Europe	CE marked, EN 55022:1998 class A, EN 55024

MODELS

S1708e-T	8-input, DVD-quality Ethernet video server
S1708e-T-A	With 1 bi-directional audio channel
S1708e-T-12iA	With 12 audio inputs
S1708e-T-AS	With on-board analytics
S1708e-T-A-AS	With on-board analytics and 1 bi-directional audio channel

WARRANTY

3-year limited warranty, covering parts and labor

* Product capabilities are enabled through software.

Contact your Verint representative for specific configurations, ordering codes, and pricing information.

By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice.

All marks referenced herein with the ® or TM symbol are registered trademarks or trademarks of Verint Systems Inc. or its subsidiaries. All rights reserved. All other marks are trademarks of their respective owners.

© 2006 Verint Systems Inc. All rights reserved.

Email: videosales@verint.com

Phone: 1-866-NEXTIVA

Or on the web at: www.verint.com/videosolutions

330 South Service Road, Melville, NY 11747 USA

July 2006

VERINT
POWERING ACTIONABLE INTELLIGENCE®