

V400-D2812-IR OUTDOOR ANALOGUE DOME CAMERA

- **1/3" Camera (Sony Effio-E)**
- **Mechanical Focus Adjustment**
- **ATR (Adaptive Tone Reproduction)**
- **High Light Compensation (HLC)**
- **2D Noise Reduction**
- **Privacy Mask**
- **Motion Detection**
- **Second Video**
- **IP66 Rated**



CCD	1/3" 960H Exview HAD II CCD
DSP	Enhanced Effio-E
TVL	COLOUR: 650TVL , B/W: 700TVL
Lens	2.8-12mm Varifocal
IR Range	Up to 30M
IR LEDs	30 PCS
Minimum Illumination	0 Lux (IR ON)
Gamma Correction	0.45
Video Output	1Vp-p,75Ω
Effective Pixels	PAL: 976 (H) × 582 (V), NTSC: 976 (H) × 494 (V)
Auto Electric Shutter	PAL:1/50-1/100,000S NTSC:1/60-1/100,000S
White Balance	ATW/PUSH/USER1/USER2/ANTI CR/ MANUAL/PUSH LOCK
Back Light Compensation	BLC & HSBLC & ATR (Adaptive Tone Reproduction)
Day/Night	Auto / COLOUR / B&W / Infrared LED exposure optimization
Motion Detection	ON/OFF(4 Zone)
Privacy Masking	ON / OFF (8 Marks)
Language	English/Japanese/Chinese/German/French/ Russian/Portuguese/Spanish
Menu	OSD Control Built-in, Second Video, Baluns
S/N Ratio	52dB (AGC OFF)
Automatic Gain Control	AUTO (4STEP)
Dynamic Noise Reduction	2D-NR
IP Rating	IP66
Power Supply	DC12V, AC24V, Dual Power Voltage
Scanning System	2:1 Interlace
Current Consumption	105mA (IR OFF), 345mA (IR ON)
Storage Temperature	-20~+60°C
Operating Temperature	-10~+50°C
Weight	0.8 Kg

Dimensions

145X145X115mm

