

With the plug and play format in mind, the TXO-1291sp series is an all-weather 1.2GHz wireless video transmitter that's ready to operate right out of the box. Designed with the harshest environments in mind, this robust transmitter delivers high resolution, real time video from a rugged IP-67 all-weather enclosure.

ADVANTAGES

- Easy to install and operate
- Rugged all weather IP-67 protective enclosure
- Four user selectable channels
- Sends video from locations normally not possible , convenient or economical with cable
- Perfect for law enforcement and government video security applications
- One Year Limited Warranty



SPECIFICATIONS	TXO-1291sp
Radiated Power	1 Watt
Four User Selectable Channels	1.080GHz – 1.2GHz
Range (Line-of-Sight)	Depends on Optional Receiver and Antenna
Transmitter Antenna Type	3dB Omnidirectional Rubber Duck
Video Format	NTSC or PAL
Video Connector	BNC Female @ 75 Ohms 1 Volt P-P
Audio Connector	BNC Female @ 600 Ohms 1 Volt P-P
Temperature Range	-40°F – 170°F
Power Supply Included	12 – 14 VDC – Polarity Protected
Current Consumption	530 mA
Dimensions	7.0" x 7.0" x 4.5" Tx
Mounting Brackets	Included – Maximum 2" Diameter
Weight	0.9 kg or 32 oz Tx
FCC / IC Approved	N/A – Amateur Radio, Law Enforcement, Government and Export

KIT INCLUDES

- All Weather Transmitter
- 12 VDC Power Supply
- Mounting Brackets
- One Year Limited Warranty
- Operating Instructions

Requires Optional Receiver and Not Included.

