

## DS19LED-PQ

19" (4:3) LED Monitor

### DS19LED-PQ

Panel Type	19" (4:3) LED Monitor
Case Type	Plastic
Maximum Resolution	1280 (H) x 1024 (V)
Active Display Area	376.32 ( H ) × 301.06 ( V ) mm
Pixel Pitch	0.294 x 0.294 mm
Bezel Thickness	Sides: 24.3mm Top: 21.3mm Bottom: 22.3mm
Contrast Ratio	1000 : 1
Brightness	250 cd/m <sup>2</sup>
Response Time	5ms
Viewing Angle	U/D: 85° / 85°, L/R: 89° / 89°
Display Colours	16.7 M
Video Synchronization	TTL Positive or Negative
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V)
Adjustable Colour Temperature	9300 K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	4:3
VGA Auto Frequency correction	Yes
Speaker	Multimedia Speakers
Number of Speakers	Right x 1 Left x 1, 2.5W
Sound Demodulation	Stereo, Audio
Mute	Yes
Work Humidity	20 % - 70 %
Work Temperature	-10 to 50 °C
Volume +/- Power On/Off	Yes



### POWER

Power Supply	12VDC, 3 amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	<30W in 'ON' mode

### OSD CONTROLS

Contrast, Brightness, OSD Duration, H-Position, V-Position, Language, Colour Temp, Backlight, Sleep Timer, Sound, Memory Recall.

### OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish and Portuguese

### ACCESSORIES

Power Supply / Kettle Lead / VGA Cable / Audio Cable / User Manual

### IN/OUT INTERFACE

Video Interface	HDMI x1 VGA x 1 BNC x 2 In / BNC x1 Out
Audio Interface	Audio In x 1, Audio L x 1, Audio R x 1
Power Interface	AC In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	Energy Star / CE / FCC / ROHS / WEEE
Vesa Standard Mount	100 x 100mm
Stand Type	Desktop
Colour	Black
Button Position	Right Hand Side
Packing Dimension	480 (W) x 500 (H) x 165 (D) mm
NET Weight	3.3 Kg
GROSS Weight	4.7 Kg

