

DS19SDI

18.51" (16:9) LED Monitor

DS19SDI

Panel Type	18.51" (16:9) LED Monitor
Case Type	Metal
Maximum Resolution	1920 (H) x 1080 (V)
Active Display Area	411.6 (H) x 232.2 (V) mm
Pixel Pitch	0.1 (H) x 0.3 (V) mm
Contrast Ratio	1000:1
Brightness	250 cd/m ²
Response Time	1.1 - 3.9 ms
Viewing Angle	U/D: 85° / 85° L/R: 88° / 88°
Display Colours	16.7 M
Video Synchronization	TTL Positive or Negative
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V)
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	16:9 Ratio With 4:3 Function
VGA Auto Frequency correction	Yes
Speaker	Multimedia Speakers
Number of Speakers	Right x 1, Left x 1, 2.5W
Sound Demodulation	Stereo, Audio
Mute	Yes
Work Humidity	20% - 70%
Work Temperature	-10 to 50 °C
Volume +/- Power On/Off	Yes



POWER

Power Supply	12VDC, 3amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	< 35W in "ON" Mode

OSD CONTROLS

Contrast, Brightness, OSD Duration, H-Position, V-Position, Language, Picture Mode, Colour Temp, Scale, Saturation, Backlight, Sleep Timer, Sound, Memory Recall, 3D NR, MPEG NR, PIP, POP

OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish and Portuguese

ACCESSORIES

Power Supply / Kettle Lead / VGA Cable / Audio Cable / User Manual / Remote Control

IN/OUT INTERFACE

Video Interface	HDMI x1 VGA x 1 S-Video BNC x 2 In / BNC x 2 Out, SDI IN / SDI OUT
Audio Interface	Audio In x 1, Audio L x 1, Audio R x 1
Power Interface	AC In x 1
Termination	75 Ohms (Automatic Termination)
Safety & EMC Certification	Energy Star / CE / FCC / ROHS / WEEE
Vesa Standard Mount	100 x 100mm
Stand Type	Picture Frame
Colour	Black
Button Position	Front, Right
Packing Dimension	530 (W) x 460 (H) x 150 (D) mm
NET Weight	3.8 Kg
GROSS Weight	4.8 Kg



